PRODUCT SHEET BRENNUS Helmet



Area of use

A protective helmet designed for various building, public works and industry trades.





Polyethylene cap

Textile cap

Features

The BRENNUS is comprised of:

- a skullcap made from die-cast polyethylene:
 - with BTP type adjustable vents
 - without EBT type vents
- a harness comprising:
 - a cap made from low density polyethylene, or a cap made from textile braids
 - a headband with a sliding nape strap, made from low density polyethylene, which is detachable and adjustable from 53 to 63 cm, or with a rack and pinion nape strap which is adjustable from 49 to 63 cm, fitted with 32 cm comfort lining

Colours: helmet with vents: white, yellow, orange, green, blue, red, fluorescent yellow. Helmet without vents: white, other colours with at least 200 parts



Weight: 330 g

The date of manufacture, usage limits and batch number are engraved onto the helmet's visor.

Duration of use: 36 months

Tests

The protective helmet complies with the NFEN 397 standard and the following optional requirements:

- resistant to very low temperatures, -20°C
- electrical isolation on the model without vents (EBT),
 440V~ symbol

The protective helmet complies with the NFEN 50365 standard:

• 5,000 V dielectric strength test and 10,000 V pot test on the model without vents (EBT), **double triangle symbol - class 0**

> AET (helmet) 0069/478/158/07/08/08305 AET (helmet) 0069/478/158/05/07/07029 PV PREN 50365 (helmet) 14/05125/UTAC MARQUE NF - Licence 107A00



20,000 V dielectric strength test and 30,000 V pot test on the model without vents (EBT).

The protective helmet has obtained the right to use the NF mark, whose requirements are:

- impact and penetration upon ageing in all colours
- port height adjustment and centering in the skullcap
- mandatory comfort lining
- lateral clearance
- lateral stiffness
- mandatory devices for fitting accessories
- periodic inspections by the French national organisation for standardisation

Accessories

An anti-noise device, mesh face shields made from polycarbonate or acetate, a lamp holder and wire guide, a headlamp, a textile cap, a sliding headband, a rack and pinion headband, a 12 or 20 mm cotton or leather chin strap, a sheepskin cap bottom, a cleanliness cap and an anti-cold cap.

Markings

The helmet can have front (55 x 50 mm), side (110 x 18 mm) or rear (50 x 30 mm) marking through hot stamping or transferring your initials or company name.





Headband with a rack and pinion nape strap



NFEN 397 NFEN 50365 36 months 330 g