



PRODUCT NUMBER: 6246121
BACOU SILVEX S3 CI SRC

- Oiled full grain leather upper. Warm fleece lining. PU2D outsole injected. SRC certified. 200J Spacium™ toe cap in injected polymer. Stainless steel anti-puncture sole. Complies with EN ISO 20345:2011 standard

Honeywell

Overview

Reference Number

6246121

Product Type

Footwear

Range

bacouoriginal

Brand

Honeywell

Brand formerly known as

BACOU

Industry

- Administration
- Building and Construction
- General Industry
- Industrial Cleaning
- Logistics
- Maintenance
- Services
- Transportation
- Utilities

Product Use

- Safety boots for professional use. The boots guarantee safety and comfort whilst ensuring high performance in the most aggressive and diverse environments. Particularly recommended for construction work & cold environments. Available in a wide range of sizes.

Features & Benefits

Feature

EN ISO 20345:2011 certified. SRC certified.

Benefit

Ensures better protection.

Feature

Oiled full grain leather upper

Benefit

Great resistance and flexibility

Feature

Water resistance

Benefit

Perfectly suited to humid environments

Feature

Extra-wide pull-on lugs

Benefit

Easy to put on & take off

Feature

Warm fleece lining

Benefit

Excellent foot insulation from the cold (CI), ideal for long periods of work on cold or frozen ground

Feature

Few lateral seams

Benefit

Upper is more resistant in extreme environments

Technical Description

Sizes

EU: 35 - 49 / UK: 3 - 13,5

Table Size

table_size_2749_id_2576

Midsole

Stainless steel: efficient technology covering the most extensive panel of risks. Puncture resistance: over 1100 N with a spike of 4.5 mm.

Upper

Oiled full grain leather. Extra-wide pull-on lugs. Warm fleece lining. Few lateral seams

Toe Cap

200J SPACIUM™ toe cap in injected polymer. Non-metallic: 50% lighter than steel. Extra-wide for greater comfort: suits all foot types. Non magnetic. Thermal insulator. Unalterable.

Insole

Dual density PU foam for intensive use. Removeable for easy care. Antibacterial for a longer life span and to prevent odour. Antistatic for optimal efficiency. Comfortable heel pads. Evacuation channels.

Outsole

Dual density polyurethane: PU 2D. Comfort layer of density: 0.5 (guarantees lightness and flexibility, ensures shock absorption and protects against changes in temperature). Outsole layer of density: 1 (resistance to abrasion, fuel oil and grease). High slip resistance due to well defined cleat design, wide, deep and self-cleaning. SRC certified: SRA: on ceramic plates : flat 0,45 (minimum standard: 0,32) heel 0,46 (minimum standard: 0,28) / SRB: on steel floor: flat 0,24 (minimum standard: 0,18), heel 0.24 (minimum standard: 0.13). Energy absorption capacity > 20 joules. Excellent resistance to abrasion: volume loss < 150 mm³ (with a load of 10 N = 1 kg). Extension before tearing: 650%. Optimised resistance to repeated flexing > 60,000 (standard >30,000). Resistant to acids and alkalis: limited to low concentrations.

Additional Features

- CI
- SRC

Certifications

E.C. Declaration of Conformity

EC Category PPE

2

Quality Assurance

ISO 9001 / 2008

EC Certificate Number

0075/797/161/04/12/0262 ext 02/04/12

EC Attestation

 EC Attestation

REACH

EU Regulation 1907/2006 (REACH) Compliance	
The substance(s) listed below may be contained in this product above the threshold level of 0.1% by weight of the listed article.	
Product Reference Sold in Europe	Substance > 0.1%
Substance Name	CAS Number
No Substance Content	

Additional Information**User Manual**

User Instruction EN ISO 20345 2011-Footwear-Honeywell-032012

Maintenance**Life Cycle**

- We advise that the footwear should be used in the limit of 3 years following the manufacturing date, which figures on the footwear.
- After this time limit, certain factors such as: exposure to sunlight, hydrometry, temperature changes, could cause a modification in the structure of the material, which would no longer maintain the same performance levels with regards to the requirements defined in the European Directive 89.686 CEE.

Storage Information

- Footwear should be stored in their original packaging, kept in a controlled stock area, not subject to rapid changes in temperature or humidity levels.

Care Instructions

- After use leave your footwear to dry in an aired place away from heat. Remove any excess dust or dirt with a brush. Remove any marks using a damp cloth and soap if necessary.
- Finally polish any grain or pigmented leathers using a commercially available shoe care product.