



CP3450-12AA5 - Productivité - Ergonomie - Innovation



Avantages utilisateurs

- ▶ Industrial angle wheel grinder
- ▶ High productivity
- ▶ Industrial grade durability up to 1000 hours maintenance intervals
- ▶ Light body



Caractéristiques

- ▶ Constant lubrication bevel gear design
- ▶ Low profile angle head design
- ▶ Insulating composite cover
- ▶ 5" (125 mm) wheel capacity
- ▶ 1.1 hp (810 W) high torque motor
- ▶ 12,000 rpm free speed
- ▶ M14 spindle
- ▶ Orientable safety lever
- ▶ Optional low vibration side handle
- ▶ Rear exhaust

Caractéristiques techniques

Code article	6151604040	
Modèle	CP3450-12AA5	
Arbre fileté	M14	
Capacité maxi. meule	125 mm	5"
Diamètre de la meule boisseaux	-	-
VSTFreeSpeed_rpm	12000 tr/min	
Vit. à vide	12000 tr/min	
VSTPower_W	810 W	
Puissance	810 W	1.1 hp
Longueur	231 mm	9.2"
Poids	1.7 kg	3.7 lb
Echappement arrière	Echappement arrière	
Niveau de bruit	95 db(A)	

Puissance sonore	106 db(A)	
Vibrations (ISO-8662-4)	5.96 m/s ²	
Vibrations α (ISO-28927-1)	8.1 m/s ²	
Vibrations K (ISO-28927-1)	2.9 m/s ²	
Consommation d'air moyenne	8.5 l/s	18.02 cfm
Consommation d'air moyenne	510 l/mn	18.02 cfm
VSTActualAirConsumption_Is	17 l/s	
Consommation d'air	17 l/s	36.04 cfm
Consommation d'air réelle	1020 l/mn	36.04 cfm
VSTFreeSpeedAirConsumption_Is	18.2 l/s	
Consommation d'air à vide	18.2 l/s	38.59 cfm
Diamètre intérieur	10 mm	3/8"
Entrée d'air	3/8	
Dimensions de l'emballage	250x155x107	