



SIZE	ART. NO.	EAN NO.
7	683a-7	7340118316628
8	683a-8	7340118316642
9	683a-9	7340118316666
10	683a-10	7340118316581
11	683a-11	7340118316604

## TEGERA® 683A

Synthetic glove, nitrile, 3/4 dipped, acrylic, polyester, 10 gg, 13 gg, sandy finish, Cat. II, yellow high-viz, black, high-viz colour, water and oil repellent palm and knuckle, for allround work

### PROPERTIES

Good grip in oily environments, warm

### SPECIFICATION

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11

LINER MATERIAL Acrylic, polyester, 10 gg, 13 gg

DIPPING 3/4 dipped

DIPPING MATERIAL Nitrile

DEXTERITY 5

GRIP PATTERN Sandy finish

CUFF STYLE Knitwrist cuff

LENGTH RANGE 240-280 mm

COLOUR Yellow high-viz, black

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Hook with hangtag

OUTER MATERIAL SPECIFICATION Nitrile, polyester

INNER MATERIAL SPECIFICATION Acrylic

1(3)

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## TEGERA® 683A

### FEATURES

High-viz colour, water and oil repellent palm and knuckle

### PRIMARY PROTECTION

Prevents risk of, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with moisture, contact with oil, contact with cold

### PRIMARY ENVIRONMENTS OF USE

Outdoors, dry environments, cold environments, wet environments, moist environments, oil and greasy environments

### PRIMARY AREAS OF USE

Assembly, building and construction, gardening, fishing industry work, foodstuff handling

### PRIMARY INDUSTRIES OF USE

Agriculture, oil, gas, petrochemical, machinery and equipment, MRO, building and construction

### TYPE OF WORK

Heavy weight



**CE** Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-03-22

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## TEGERA® 683A

### EC TYPE EXAMINATION

Notified Body: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07 France

### COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to wear (No. of revolutions)	4	(4)
B) Resistance to cutting (Index)	3	(5)
C) Tear resistance (Newton)	3	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection	1	2	3	4	5
A) Resistance to wear (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 511:2006 Protective gloves against cold



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-03-22

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com