

Art. 241

Réduction simple MF

MF reducing bush

Reducción corta MH

CŒUR BLANC
WHITEHEART
NÚCLEO BLANCO




ISO/EN : **N4**

Index : **241**



Ø1	Ø2	Dimension a	Finition finishing acabado			
			Noire black negro		Galva.	
			Ref.	kg	Ref.	kg
1/4"	1/8"	20	-	-	1502410080500 *	0,008
3/8"	1/8"	20	-	-	1502410120500 *	0,017
	1/4"	20	1002410012800	0,018	1502410012800	0,019
1/2"	1/8"	24	-	0,033	1502410150500 *	0,033
	1/4"	24	1002410015800	0,039	1502410015800	0,039
	3/8"	24	1002410151200	0,031	1502410151200	0,032
3/4"	1/4"	26	1002410200800	0,062	1502410200800	0,065
	3/8"	26	1002410201200	0,058	1502410201200	0,060
	1/2"	26	1002410201500	0,052	1502410201500	0,052
1"	3/8"	29	1002410261200	0,101	1502410261200	0,100
	1/2"	29	1002410261500	0,102	1502410261500	0,106
	3/4"	29	1002410262000	0,082	1502410262000	0,084
1"1/4	3/8"	29	1002410331200	0,180	1502410331200	0,209
	1/2"	31	1002410331500	0,190	1502410331500	0,213
	3/4"	31	1002410332000	0,177	1502410332000	0,184
	1"	31	1002410332600	0,142	1502410332600	0,140
1"1/2	1/2"	31	1002410401500	0,245	1502410401500	0,254
	3/4"	31	1002410402000	0,240	1502410402000	0,255
	1"	31	1002410402600	0,210	1502410402600	0,220
	1"1/4	31	1002410403300	0,150	1502410403300	0,150
2"	1/2"	35	1002410501500	0,360	1502410501500	0,365
	3/4"	35	1002410502000	0,370	1502410502000	0,380
	1"	35	1002410502600	0,365	1502410502600	0,380
	1"1/4	35	1002410503300	0,365	1502410503300	0,340
	1"1/2	35	1002410504000	0,300	1502410504000	0,305
2"1/2	1"	40	1002410662600	0,570	1502410662600	0,590
	1"1/4	40	1002410663300	0,590	1502410663300	0,590
	1"1/2	40	1002410664000	0,570	1502410664000	0,555
	2"	40	1002410665000	0,455	1502410665000	0,465
3"	1"	44	1002410802600	0,830	1502410802600	0,850
	1"1/4	44	1002410803300	0,850	1502410803300	0,890
	1"1/2	44	1002410804000	0,830	1502410804000	0,840
	2"	44	1002410805000	0,805	1502410805000	0,830
	2"1/2	44	1002410806600	0,590	1502410806600	0,610
	3"	44	1002410808000	1,300	1502410808000	1,360
4"	1"1/2	51	1002411024000	1,553	1502411024000	1,540
	2"	51	1002411025000	1,605	1502411025000	1,610
	2"1/2	51	1002411026600	1,535	1502411026600	1,600
	3"	51	1002411028000	1,300	1502411028000	1,360



* Modèle en acier selon norme EN 10241

* Steel design acc. to EN 10241 standard

* Modelo de acero según norma EN 10241