

Art. 300

Bouchon femelle

Female cap

Tapón hembra

CŒUR BLANC
WHITEHEART
NÚCLEO BLANCO




ISO/EN : **T1**

Index : **300**



Ø	Dimension a	Finition finishing acabado			
		Noire black negro		Galva.	
		Ref.	kg	Ref.	kg
1/4"	15	1003000000800	0,025	1503000000800	0,027
3/8"	17	1003000001200	0,032	1503000001200	0,034
1/2"	22,5	1003000001500	0,055	1503000001500	0,058
3/4"	25	1003000002000	0,079	1503000002000	0,084
1"	27,5	1003000002600	0,143	1503000002600	0,145
1"1/4	30	1003000003300	0,205	1503000003300	0,210
1"1/2	30	1003000004000	0,230	1503000004000	0,240
2"	35,5	1003000005000	0,445	1503000005000	0,477
2"1/2	36,5	1003000006600	0,655	1503000006600	0,670
3"	39,5	1003000008000	0,950	1503000008000	0,990
4"	56,5	1003000010200	1,820	1503000010200	1,670



Art. 290

Bouchon mâle avec butée

Flanged plug

Tapón macho con tope

CŒUR BLANC
WHITEHEART
NÚCLEO BLANCO




ISO/EN : **T9**

Index : **290**



Ø	Dimension a	Finition finishing acabado			
		Noire black negro		Galva.	
		Ref.	kg	Ref.	kg
1/8"	14	-	-	1502900000500 *	0,007
1/4"	22	1002900000800	0,024	1502900000800	0,024
3/8"	24	1002900001200	0,034	1502900001200	0,035
1/2"	26	1002900001500	0,052	1502900001500	0,054
3/4"	32	1002900002000	0,074	1502900002000	0,076
1"	36	1002900002600	0,144	1502900002600	0,137
1"1/4	39	1002900003300	0,190	1502900003300	0,195
1"1/2	41	1002900004000	0,205	1502900004000	0,203
2"	48	1002900005000	0,390	1502900005000	0,400
2"1/2	54	1002900006600	0,665	1502900006600	0,592
3"	60	1002900008000	0,800	1502900008000	0,786
4"	70	1002900010200	1,425	1502900010200	1,500



* Modèle en acier selon norme EN 10241

* Steel design acc. to EN 10241 standard

* Modelo de acero según norma EN 10241