MOULD PROTECT

Technical Data Sheet

Product name: Mould Protect Creation date: 01/02/2017 Version: 1

Replaces: 0

1: General description

Transparent long-term corrosion inhibitor for protection of mould tools during storage and shipping.

2: Features

Thanks to its low surface tension, CRC Mould Protect repels humidity on metal surfaces. It lays down a high quality wax-like film, which assures a long-lasting efficient protection.

- Long term waxy protection
- High covering power.
- Neutralizes fingerprints.
- Does not contain silicones
- Chemically inert to alloys and non-ferrous metals

3: Applications

- Protection of moulds during longer periods of inactivity.
- Protection of machine parts which might come in contact with aggressive products like during the transformation of PVC.

4: Directions

- Sufaces should be degreased, clean and dry, prior to application
- Spray an even coat and re-apply as necessary.
- Mould surfaces and extrusion parts should be cleaned before bringing into operation again.

A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.

5: Typical product data (without propellant)

Colour
Odour
Density (at 20°C)
Transparent
Characteristic
0.68 g/cm³



6: Packaging

Aerosol I2x500 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.