

Adaptateurs




Figure 1




Figure 2




Figure 3




Figure 4

Série 280

Jonction en T taraudée

Connexion F	Connexion F1	Référence	Fig.	Dimensions		Hexagone	Poids
				L	L1		
				(mm)	(mm)	(mm)	(g)
G 1/8	-	ML0028018	1	28	42	-	28
G 1/4	-	ML0028014	1	34	51	-	57
G 3/8	-	ML0028038	1	39	56	-	83
G 1/2	-	ML0028012	1	46	67	-	144
G 3/4	-	ML0028034	1	53	73	-	201
G 1	-	ML0028010	1	64	90	-	321

Jonction en Y taraudée

Connexion F	Connexion F1	Référence	Fig.	Dimensions		Hexagone	Poids
				L	L1		
				(mm)	(mm)	(mm)	(g)
G 1/8	-	ML0028618	2	27	29	13	19
G 1/4	-	ML0028614	2	32	36	17	34
G 3/8	-	ML0028638	2	37	41	20	44
G 1/2	-	ML0028612	2	45	53	25	93

Jonction en croix taraudée

Connexion F	Connexion F1	Référence	Fig.	Dimensions		Hexagone	Poids
				L	L1		
				(mm)	(mm)	(mm)	(g)
G 1/8	-	ML0028118	3	42	-	-	48
G 1/4	-	ML0028114	3	51	-	-	73
G 3/8	-	ML0028138	3	56	-	-	107
G 1/2	-	ML0028112	3	67	-	-	185

Coude femelle à 90 °

Connexion F	Connexion F1	Référence	Fig.	Dimensions		Hexagone	Poids
				L	L1		
				(mm)	(mm)	(mm)	(g)
G 1/8	-	ML0028218	4	28	-	-	21
G 1/4	-	ML0028214	4	34	-	-	40
G 3/8	-	ML0028238	4	39	-	-	58
G 1/2	-	ML0028212	4	47	-	-	106
G 3/4	-	ML0028234	4	50	-	-	130
G 1	-	ML0028210	4	64	-	-	227