

eSMART107 Tech-Note

7" TFT - ARM Cortex-A9 dual core - 800 MHz

- ARM Cortex-A9 dual-core CPU
- 7" TFT color display, resolution 800x480 pixel, 64K colors. Dimmable LED backlight
- Resistive touchscreen
- 2 Ethernet ports
- 2 CAN ports
- 4 Serial ports
- 2 USB ports



Highlights

eSMART107 combines top performance and plenty connectivity features in a compact design.

It is an ideal platform for integrated HMI and control applications. The product has been designed as IoT edge device with the combination of a powerful controller with networking capability and outstanding communication options including client/server OPC UA.



The eSMART HMI products have been designed to run the JMobile software.

- JMobile runtime included
- Requires JMobile V2.6 or higher
- Supports Corvina Cloud secure connectivity with full network separation
- OPC UA Server and Client
- Optional CODESYS V3 runtime with choice of EtherCAT, Profinet, Ethernet IP, Modbus TCP and CAN networks



eSMART107 - Technical Data



| System Resources | |
|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display - Colors | 7" TFT 16:9 - 64K |
| Resolution | 800x480, WVGA |
| Brightness | 200 Cd/m ² typ. |
| Dimming | to 0% |
| Touchscreen | Resistive |
| CPU | ARM Cortex-A9 dual core - 800 MHz |
| Operating System | Linux RT |
| Flash | 4 GB |
| RAM | 1 GB |
| Real Time Clock, RTC Back-up, Buzzer | Yes, Yes, No |
| Interface | |
| Ethernet port | 2 (port 0 - 10/100/1000, port 1 - 10/100) |
| USB port | 2 (Host V2.0, max. 100 mA) |
| Serial port | 2 (RS-232), 2 (RS-422/RS-485 isolated), 2 (CAN 2.0b isolated) |
| SD card | No |
| Expansion | No |
| Ratings | |
| Power supply | 24 Vdc (10 to 32 Vdc) |
| Current Consumption | 0.3 A at 24 Vdc (max.) |
| Input Protection | Electronic |
| Battery | Yes (Supercapacitor) |
| Environment Conditions | |
| Operating Temp | 0 to +50°C (vertical installation) |
| Storage Temp | -20°C to +70°C |
| Operating / Storage Humidity | 5-85% RH, non condensing |
| Protection Class | IP66 (front), IP20 (rear) Type: 2, 4X |
| Dimensions and Weights | |
| Faceplate LxH | 187x147 mm (7.36x5.79") |
| Cutout AxB | 176x136 mm (6.93x5.35") |
| Depth D+T | 29+5 mm (1.14+0.19") |
| Weight | 0.875 Kg |
| Approvals | |
| CE | Emission EN 61000-6-4, Immunity EN 61000-6-2 for installation in industrial environments Emission EN 61000-6-3, Immunity EN 61000-6-1 for installation in residential environments |
| UL | cULus: UL508 |
| DNV-GL | Yes |
| EU RO MR | Yes |
| RCM | Yes |



- | | |
|----------------------------|------------------------------------|
| 1 Power Supply | 6 USB port |
| 2 Serial port RS-485 + CAN | 7 Ethernet port 0 (10/100/1000 Mb) |
| 3 Serial port RS-485 + CAN | 8 Ethernet port 1 (10/100 Mb) |
| 4 Serial port 2x RS-232 | 9 DIP switch port configuration |
| 5 USB port | 10 DIP switch port configuration |



Cut-out

Ordering Information

| Model | Part Number | Description |
|-----------|--------------|-------------------------------------------------------------------------------------------------------------|
| eSMART107 | +ESMA107U301 | 7" TFT color with touchscreen. 2 Ethernet ports, 2 CAN ports, 4 serial ports, 2 USB ports. JMobile runtime. |