



Cristallo Extra



GB

APPLICATIONS AND REGULATIONS

Hose for food liquids transport without pressure, in compliance with the European regulation Reg. (EU) 10/2011, for simulants A, B and C. In compliance with the KTW guidelines for the contact with drinkable water.

STRUCTURE

Flexible PVC hose without reinforcement.

WORKING TEMPERATURE

From -20°C to +60°C

D

ANWENDUNGEN UND RICHTLINIEN

Schlauch für den durchgang von flüssigen lebensmitteln ohne druck nach der Europäischen Richtlinie Reg. (EU) 10/2011, für Simulanten A-B-C und der Richtlinie KTW für das Trinkwasser.

STRUKTUR

Flexibler PVC-Schlauch, ohne Verstärkung.

TEMPERATURBESTÄNDIGKEIT

Von -20°C bis +60°C

I

APPLICAZIONI E NORMATIVE

Tubo per passaggio di liquidi alimentari non in pressione secondo la Direttiva Europea Reg. (EU) 10/2011 per i Simulanti A-B-C. Conforme alla linee guida per il contatto con acqua potabile KTW.

STRUTTURA

Tubo flessibile in PVC non rinforzato.

TEMPERATURA D'UTILIZZO

Da -20°C a +60°C

F

APPLICATIONS ET DIRECTIVES

Tuyau pour le passage de liquides alimentaires sans pression selon la Directive Européenne Reg. (EU) 10/2011, pour les simulants A-B-C. Conforme aux directives KTW pour le contact avec l'eau potable.

STRUCTURE

Tuyau flexible en PVC sans renforcement textile.

TEMPERATURE D'EMPLOI

À partir de -20°C jusqu'à +60°C



Test report obtained from a qualified institute
 Test report conseguito da laboratorio accreditato.
 Testbericht wurde von einem anerkannten Institut ausgestellt
 Rapports d'essais obtenus par le laboratoire accrédité.

Ø Inside mm	Ø Outside mm	Thickness mm	Working pressure bar *	Bursting Pressure bar *	Length m	Weight per meter g/m	PCS pallet	Pallet size
2	4	1	-	-	100	12	200	80x120
3	5	1	-	-	100	15	150	80x120
3	6	1,5	-	-	100	26	120	80x120
4	6	1	-	-	100	19	120	80x120
4	7	1,5	-	-	50	32	96	80x120
4	7	1,5	-	-	100	32	110	80x120
5	7	1	-	-	100	23	64	80x120
5	8	1,5	-	-	50	37	96	80x120
5	8	1,5	-	-	100	37	48	80x120
6	8	1	-	-	100	27	48	80x120
6	9	1,5	-	-	50	43	96	80x120
6	9	1,5	-	-	100	43	48	80x120
6	10	2	-	-	100	62	48	80x120
7	9	1	-	-	100	30	54	80x120
7	10	1,5	-	-	100	49	48	80x120
8	10	1	-	-	100	35	42	80x120
8	10	1	-	-	50	35	54	80x120
8	11	1,5	-	-	100	55	42	80x120
8	12	2	-	-	100	77	42	80x120
8	12	2	-	-	50	77	64	80x120
9	13	2	-	-	100	84	30	80x120
9	13	2	-	-	50	84	60	80x120
10	13	1,5	-	-	50	66	36	80x120
10	14	2	-	-	50	92	42	80x120
12	16	2	-	-	50	107	42	80x120
13	17	2	-	-	50	112	36	80x120
13	19	3	-	-	50	184	36	80x120
14	18	2	-	-	50	123	36	80x120
15	19	2	-	-	50	130	24	80x120
16	20	2	-	-	50	138	24	80x120
18	23	2,5	-	-	50	196	16	80x120
19	24	2,5	-	-	50	206	12	80x120
20	25	2,5	-	-	50	212	10	80x120
20	26	3	-	-	50	260	10	80x120
22	28	3	-	-	50	282	8	80x120
25	31	3	-	-	50	318	8	80x120
25	33	4	-	-	50	436	8	80x120
30	38	4	-	-	25	514	7	80x120

Ø Inside mm	Ø Outside mm	Thickness mm	Working pressure bar *	Bursting Pressure bar *	Length m	Weight per meter g/m	PCS pallet	Pallet size
32	40	4	-	-	25	543	8	80x120
35	43	4	-	-	25	590	7	80x120
38	48	5	-	-	25	808	6	80x120
40	49	4,5	-	-	25	752	5	120x120
50	60	5	-	-	25	1032	5	120x120
60	70	5	-	-	25	1226	5	2 plt 80x160

* Working and bursting pressure at 20°C

Inner diameters and corresponding tolerances according to the norm UNI EN ISO 1307:2008
 It is to emphasize that since thermoplastic products are subject to deformations and shrinkings also due to the outside temperature, the length tolerance is ± 5%