

REDSPIR SAF SPH

Phthalate-free low temperature medium duty flexible hose for suction and delivery of liquids & foodstuffs

Tuyau flexible à basse température de qualité alimentaire sans phtalate pour le pompage et le refoulement de liquides pour un usage soutenu



Structure : Flexible hose made out of phthalate-free, very soft, low temperature resistant, food-grade PVC wall in accordance with the modified EU regulation 10/2011, reinforced with shock-resistant PVC spiral.








Applications : Designed for low temperature, medium duty suction and delivery of high quality liquids & foodstuffs, fruit juice, wine, beer and alcohol up to 50%, compatible with PVC.



Structure : Tuyau flexible fait d'une paroi PVC très souple sans Phtalate de qualité alimentaire selon la norme 10/2011 modifiée, renforcé d'une spirale en PVC rigide de qualité antichoc.

Applications : Conçu pour une utilisation soutenue à basse température d'aspiration et de refoulement de liquides alimentaires de forte valeur ajoutée, incluant l'alcool à 50%, compatibles avec le PVC.

IANESCO certificate available on request | Certificat IANESCO disponible sur demande

						
int mm	ext mm	kg/m	mm	bar	bar	m
35	43,0	0,595	225	9	0,90	25
40	48,6	0,760	234	9	0,90	25
51	60,0	1,050	243	8	0,90	25
55	64,2	1,125	252	8	0,85	25
60	69,4	1,240	270	8	0,85	25
63	72,3	1,230	292	7	0,85	25
70	80,2	1,650	342	7	0,85	25
80	92,0	1,875	360	7	0,85	25
90	103,0	2,200	405	5	0,85	25
102	114,0	2,815	450	4	0,85	25
110	124,4	3,125	477	4	0,80	25
120	136,0	3,585	540	4	0,80	25
152	168,0	5,125	675	3	0,80	25



Phthalate Free!

Printing | Marquage :

REDSPIR SAF SPH  PHTHALATE FREE CE 10/2011 n°lot

Temperature | Température :

-25 / + 55 °C
-13 / + 131 °F

Properties | Caractéristiques :

Smooth inside, smooth outside.
Lisse intérieur, lisse extérieur.

Colors | Couleurs :

