



**Bouchons mâles femelles BMF** (concernant les bouchons destinés au montage sur accessoires à joints, voir en bas de page)

Dimensions (mm)	5030 Galva standard		5030 Galva avec joints		5030 Aluminium standard	
	REF	CODE	REF	CODE	REF	CODE
Ø D						
80	BMF 80	523 220	-	-	-	-
100	BMF 100	523 440	-	-	BMF 100 AL	533 695
125	BMF 125	523 441	BMF 125 J	547 368	BMF 125 AL	523 937
160	BMF 160	523 442	BMF 160 J	547 352	BMF 160 AL	523 938
200	BMF 200	523 443	BMF 200 J	529 111	BMF 200 AL	523 939
250	BMF 250	523 444	BMF 250 J	529 112	BMF 250 AL	523 940
315	BMF 315	523 445	BMF 315 J	529 186	BMF 315 AL	523 941
355	BMF 355	523 448	BMF 355 J	529 192	BMF 355 AL	523 756
400	BMF 400	523 446	BMF 400 J	547 540	BMF 400 AL	523 757
450	BMF 450	524 010	BMF 450 J	547 560	-	-
500	BMF 500	523 447	BMF 500 J	547 529	BMF 500 AL	523 758
560	BMF 560	543 300	BMF 560 J	547 649	-	-
630	BMF 630	523 987	BMF 630 J	547 302	-	-
710	BMF 710	543 301	-	-	-	-
800	BMF 800	543 302	-	-	-	-
900	BMF 900	523 414	-	-	-	-



**Bouchons mâles grillagés**

Dimensions (mm)	5030 Galva standard	
	REF	CODE
Ø D		
100	BMF 100 G	547 474
125	BMF 125 G	547 475
160	BMF 160 G	547 476
200	BMF 200 G	547 477
250	BMF 250 G	547 478
315	BMF 315 G	547 479
355	BMF 355 G	547 480
400	BMF 400 G	547 482
450	BMF 450 G	547 483
500	BMF 500 G	547 484
560	BMF 560 G	547 485
630	BMF 630 G	547 486
710	BMF 710 G	547 487



**Bouchons alu femelle avec purge**

5030 Aluminium standard	
REF	CODE
BMF 125 AL/P	547 039
BMF 160 AL/P	547 030
BMF 200 AL/P	547 031
BMF 250 AL/P	547 032
BMF 315 AL/P	547 040
BMF 400 AL/P	547 041



**Bouchons femelles**  
pour montage sur accessoires à joints

5030 Galva standard	
REF	CODE
BF 125	525 291
BF 160	525 292
BF 200	525 293
BF 250	525 294
BF 315	525 295
BF 355	525 296
BF 400	525 297
BF 450	525 298