



EN AW-5019 [AlMg5]

d	l+1	$\frac{k}{d}$	N°		
<b>3,2</b>	6,5	0,5 - 2,0	10900032065	500	
	8,0	1,5 - 3,5	10900032080	500	
	9,5	3,0 - 5,0	10900032095	500	
	11,0	4,5 - 6,5	10900032110	500	
	12,5	6,0 - 8,0	10900032125	500	
<b>dk</b> 6,0 -0,3	<b>dm</b> 1,7	<b>k</b> 1,1 ±0,15	3,3 mm	1100 N	1450 N
<b>4,0</b>	8,0	0,5 - 3,5	10900040080	500	
	9,5	3,0 - 5,0	10900040095	500	
	11,0	4,5 - 6,5	10900040110	500	
	12,5	6,0 - 8,0	10900040125	500	
	14,5	7,5 - 10,0	10900040145	500	
<b>dk</b> 8,0 -0,4	<b>dm</b> 2,2	<b>k</b> 1,3 ±0,2	4,1 mm	1700 N	2700 N

d	l+1	$\frac{k}{d}$	N°		
<b>4,8</b>	8,5	0,5 - 3,5	10900048085	500	
	9,5	3,0 - 5,0	10900048095	500	
	11,0	4,5 - 6,5	10900048110	500	
	13,0	6,0 - 8,0	10900048130	500	
	14,5	7,5 - 9,5	10900048145	500	
	16,0	9,0 - 11,0	10900048160	500	
	18,0	10,5 - 13,0	10900048180	500	
	21,0	12,5 - 16,0	10900048210	500	
<b>dk</b> 9,5 -0,4	<b>dm</b> 2,7	<b>k</b> 1,5 ±0,2	4,9 mm	2480 N	3540 N
<b>6,4</b>	12,5	1,5 - 6,5	10900064125	500	
	15,5	3,5 - 9,5	10900064155	500	
<b>dk</b> 13,0 -0,4	<b>dm</b> 3,7	<b>k</b> 2,0 ±0,3	6,5 mm	3760 N	5460 N