


## NATV25-PP

### Galet de roulement

Yoke type track rollers NATV..-PP-A, single row needle roller bearings with particularly thick-walled outer ring, full complement needle roller set and an inner ring, axial guidance of outer ring is provided by the plastic axial plain washers and contact washers, three-stage sealing by plastic axial plain washer on both sides

## Information technique



### Votre alternative produit actuelle

joint	PP	Joint frottant des deux côtés
profile bague extérieure	IOP	Optimized INA-profile
dispositif de lubrification	IR	Via inner ring

### dimensions principale & données de performance

d	25 mm	Alésage
D	52 mm	Diamètre extérieur
B	25 mm	Largeur, bague intérieure
C <sub>rw</sub>	20.100 N	Charge dyn. de base, radiale
C <sub>0r w</sub>	44.500 N	Charge stat. de base, radiale
C <sub>ur w</sub>	6.300 N	Limite à la fatigue, radiale
n <sub>D G</sub>	1.000 1/min	Vitesse pour une lubrification à la graisse
F <sub>0r per</sub>	44.500 N	Charge radiale statique admissible
F <sub>r per</sub>	43.500 N	Charge radial dynamique admissible sur bague extérieure
≈m	0,281 kg	Poids

### Dimensions

C	24 mm	Largeur, bague extérieure
d <sub>2</sub>	41,5 mm	Diamètre extérieur rondelle de butée
r <sub>min</sub>	1 mm	Dimension minimum de chanfrein



Afficher les détails du produit dans medias

14.10.2025, 13:07:18 CEST

SCHAFFLER

### Caractéristiques

-  Fr Effort radial
-  L<sub>h</sub> Lubrification à vie, sans entretien
-  Lubrification à la graisse
-  Etanche des 2 côtés