


## LR608-2RSR

### Galet de roulement

Yoke type track rollers LR6..-2RS/2RSR, single row self-retaining ball bearings with particularly thick-walled outer ring, ball and cage assembly and an inner ring, axial guidance of outer ring is provided by the balls, lip seal on both sides, with axial sealing action/with radial sealing action

## Information technique



### Votre alternative produit actuelle

joint	2RSR	Joint frottant des deux côtés
profile bague extérieure	R500	Diamètre extérieur sphérique (Standard)
dispositif de lubrification	Without	Without

### dimensions principale & données de performance

D	24 mm	Diamètre extérieur
d	8 mm	Alésage
C	7 mm	Hauteur
$C_{rw}$	2.950 N	Charge dyn. de base, radiale
$C_{0rw}$	1.280 N	Charge stat. de base, radiale
$C_{urw}$	64 N	Limite à la fatigue, radiale
$n_{DG}$	19.000 1/min	Vitesse pour une lubrification à la graisse
$\approx m$	0,016 kg	Poids

### Dimensions

$d_2$	10 mm	Diamètre rondelle de butée
$r_{min}$	0,3 mm	Dimension minimum de chanfrein
R	500 mm	Rayon bague extérieure profile externe



Afficher les détails du produit dans medias

14.10.2025, 12:59:51 CEST

SCHAFFLER

### Caractéristiques

-  Effort radial
-  Effort axial uni directionnel
-  Effort axial dans les 2 directions
-  Lubrification à vie, sans entretien
-  Lubrification à la graisse
-  Etanche des 2 côtés