


0105 Piquage droit, mâle BSPT

Laiton




ØD	C		F	F1	H max	H1	Kg
4	R1/8	0105 04 10	10	10	17	7	0,012
5	R1/8	0105 05 10	11	12	17,5	7,5	0,016
	R1/4	0105 05 13	14	12	17,5	7,5	0,023
6	R1/8	0105 06 10	11	13	18	7,5	0,017
	R1/4	0105 06 13	14	13	18	7,5	0,024
6	R3/8	0105 06 17	17	13	18	8,5	0,030
	R1/8	0105 08 10	13	14	19,5	7	0,021
8	R1/4	0105 08 13	14	14	19,5	7	0,026
	R3/8	0105 08 17	17	14	20,5	8	0,032
8	R1/8	0105 10 10	17	19	24	9	0,043
	R1/4	0105 10 13	17	19	24	9	0,047
10	R3/8	0105 10 17	17	19	24	9	0,048
	R1/2	0105 10 21	22	19	25	10	0,066
10	R1/4	0105 12 13	19	22	24	9	0,059
	R3/8	0105 12 17	19	22	24	9	0,060
12	R1/2	0105 12 21	22	22	25	10	0,076
	R1/4	0105 14 13	22	24	25	8	0,067
14	R3/8	0105 14 17	22	24	25	8	0,068
	R1/2	0105 14 21	22	24	26	9	0,079
14	R3/4	0105 14 27	27	24	27	10	0,106
	R3/8	0105 15 17	22	24	25	8	0,066
15	R1/2	0105 15 21	22	24	26	9	0,076
	R1/4	0105 16 13	24	27	27	9,5	0,092
16	R3/8	0105 16 17	24	27	27	9,5	0,093
	R1/2	0105 16 21	24	27	27	9,5	0,101
16	R3/4	0105 16 27	27	27	28	10,5	0,123
	R1/2	0105 18 21	27	30	30	10,5	0,128
18	R3/4	0105 18 27	27	30	30	10,5	0,140
	R1/2	0105 20 21	30	32	32	11	0,147
20	R3/4	0105 20 27	30	32	32	11	0,160
	R1/2	0105 22 21	32	36	33	11	0,188
22	R3/4	0105 22 27	32	36	33	11	0,198
	R1	0105 22 34	36	36	33	11	0,229
25	R3/4	0105 25 27	36	41	36	11	0,265
	R1	0105 25 34	36	41	36	11	0,281
28	R3/4	0105 28 27	41	42	36	11	0,273
	R1	0105 28 34	41	42	36	11	0,282

Raccords avec filetages métriques coniques ou NPT, sur commande spéciale, lorsque les quantités le justifient.

0105 Piquage droit, mâle NPT


Laiton



ØD	C		F	F1	H max	H1	Kg
6	NPT1/8	0105 06 11	11	13	18	7,5	0,018
	NPT1/4	0105 06 14	14	13	18	7,5	0,027
8	NPT1/8	0105 08 11	13	14	21	7	0,021
	NPT1/4	0105 08 14	14	14	18,5	7	0,026
10	NPT1/4	0105 10 14	17	19	24	9	0,047
	NPT3/8	0105 10 18	17	19	24	9	0,047
10	NPT1/2	0105 10 22	22	19	25	10	0,066

0101 Piquage droit avec rondelle imperdable, mâle BSPP et métrique

Laiton, polymère technique



20 bar

ØD	C		E	F	F1	H max	H1	Kg
4	M5x0,8	0101 04 19	5	10	10	16,5	8	0,011
	G1/8	0101 04 10	6,5	13	10	16,5	8	0,016
5	G1/8	0101 05 10	6,5	13	12	17,5	8,5	0,019
	G1/8	0101 06 10	6,5	13	13	18	8,5	0,020
6	G1/4	0101 06 13	8	17	13	18	9,5	0,030
	G1/8	0101 08 10	6,5	13	14	19	8,5	0,021
8	G1/4	0101 08 13	8	17	14	19,5	9	0,031
	G3/8	0101 08 17	11	22	14	20	10,5	0,043
10	G1/4	0101 10 13	8	17	19	24	11	0,048
	G3/8	0101 10 17	11	22	19	24	11,5	0,061
10	G1/4	0101 12 13	8	19	22	24	11	0,061
	G3/8	0101 12 17	11	22	22	24	11,5	0,069
12	G1/2	0101 12 21	12	27	22	24	12	0,089
	G3/8	0101 14 17	11	22	24	25	10,5	0,075
14	G1/2	0101 14 21	12	27	24	25	11	0,093
	G3/8	0101 15 17	11	22	24	25	10,5	0,071
15	G1/2	0101 15 21	12	27	24	25	11	0,093
	G3/8	0101 16 17	11	22	27	27	12	0,092
16	G1/2	0101 16 21	12	27	27	27	12,5	0,110
	G1/2	0101 18 21	12	27	30	29,5	12,5	0,131
18	G3/4	0101 18 27	13	32	30	29,5	13	0,154
	G3/4	0101 20 27	13	32	32	31	13	0,166
20	G3/4	0101 22 27	13	32	36	32	13	0,197
	G1	0101 22 34	15	41	36	31	13,5	0,259
28	G1	0101 28 34	15	41	42	35,5	13,5	0,300

Filetage avec rondelle joint. Les rondelles-joints référence 0602 se trouvent au sous chapitre "accessoires de raccordement".