


Compléments des raccords à compression en laiton


0166

Réduction trois pièces



Laiton



| ØD1 | ØD2 |  | F | kg |
|-----|-----|---|----|-------|
| 4 | 5 | 0166 04 05 | 13 | 0,011 |
| | 6 | 0166 04 06 | 13 | 0,011 |
| | 8 | 0166 04 08 | 14 | 0,012 |
| | 10 | 0166 04 10 | 19 | 0,031 |
| | 12 | 0166 04 12 | 22 | 0,044 |
| 5 | 14 | 0166 04 14 | 24 | 0,054 |
| | 15 | 0166 04 15 | 24 | 0,056 |
| | 6 | 0166 05 06 | 13 | 0,010 |
| | 8 | 0166 05 08 | 14 | 0,012 |
| | 10 | 0166 05 10 | 19 | 0,030 |
| 6 | 12 | 0166 05 12 | 22 | 0,044 |
| | 14 | 0166 05 14 | 24 | 0,053 |
| | 16 | 0166 05 16 | 27 | 0,078 |
| | 8 | 0166 06 08 | 14 | 0,012 |
| | 10 | 0166 06 10 | 19 | 0,030 |
| 8 | 12 | 0166 06 12 | 22 | 0,043 |
| | 14 | 0166 06 14 | 24 | 0,052 |
| | 15 | 0166 06 15 | 24 | 0,054 |
| | 16 | 0166 06 16 | 27 | 0,077 |
| | 10 | 0166 08 10 | 19 | 0,027 |
| 10 | 12 | 0166 08 12 | 22 | 0,040 |
| | 14 | 0166 08 14 | 24 | 0,051 |
| | 15 | 0166 08 15 | 24 | 0,053 |
| | 16 | 0166 08 16 | 27 | 0,076 |
| | 18 | 0166 08 18 | 30 | 0,100 |
| 12 | 12 | 0166 10 12 | 22 | 0,037 |
| | 14 | 0166 10 14 | 24 | 0,045 |
| | 15 | 0166 10 15 | 24 | 0,047 |
| | 16 | 0166 10 16 | 27 | 0,068 |
| | 18 | 0166 10 18 | 30 | 0,095 |
| 14 | 20 | 0166 10 20 | 32 | 0,107 |
| | 22 | 0166 10 22 | 36 | 0,144 |
| | 25 | 0166 10 25 | 41 | 0,209 |
| | 14 | 0166 12 14 | 24 | 0,043 |
| | 15 | 0166 12 15 | 24 | 0,043 |
| 15 | 16 | 0166 12 16 | 27 | 0,066 |
| | 18 | 0166 12 18 | 30 | 0,092 |
| | 20 | 0166 12 20 | 32 | 0,102 |
| | 22 | 0166 12 22 | 36 | 0,140 |
| | 25 | 0166 12 25 | 41 | 0,200 |
| 16 | 16 | 0166 14 16 | 27 | 0,060 |
| | 18 | 0166 14 18 | 30 | 0,084 |
| | 20 | 0166 14 20 | 32 | 0,095 |
| | 22 | 0166 14 22 | 36 | 0,133 |
| | 25 | 0166 14 25 | 41 | 0,189 |
| 18 | 18 | 0166 15 18 | 30 | 0,081 |
| | 22 | 0166 15 22 | 36 | 0,130 |
| | 18 | 0166 16 18 | 30 | 0,078 |
| 20 | 20 | 0166 16 20 | 32 | 0,088 |
| | 22 | 0166 16 22 | 36 | 0,126 |
| | 25 | 0166 16 25 | 41 | 0,185 |
| 22 | 20 | 0166 18 20 | 32 | 0,082 |
| | 22 | 0166 18 22 | 36 | 0,118 |
| | 25 | 0166 18 25 | 41 | 0,180 |
| | 28 | 0166 18 28 | 42 | 0,176 |
| 20 | 25 | 0166 20 25 | 41 | 0,168 |
| 22 | 28 | 0166 22 28 | 42 | 0,168 |

ØD1 : tube à monter ; ØD2 : pour raccord de Ø xx mm.

Chacune des références ci-dessus comprend 3 pièces :

- la réduction proprement dite

- la bague laiton, réf. 0124

- l'écrou