


207ACBH Traversée de cloison égale, femelle NPTF

Laiton



C		F	F1	K	L	Kg
NPTF1/8	207ACBH-2	7/8	1.5/16	20	38	0,072
NPTF1/4	207ACBH-4	1	1.1/8	18	38	0,099
NPTF3/8	207ACBH-6	1.1/8	1.1/8	13	34	0,127
NPTF1/2	207ACBH-8	1.1/4	1.3/8	16	38	0,155

*F et F1 sont des dimensions en pouces

0155 Manchon égal, femelle BSPP

Laiton



C	C1	F	L	Kg
G1/8	0155 10 10	14	17	0,014
G1/8	0155 10 13	17	18	0,022
	0155 13 13	17	24	0,025
G3/8	0155 17 17	22	25	0,045
G1/2	0155 21 21	27	32	0,084
G3/4	0155 27 27	32	35	0,108
G1	0155 34 34	41	36	0,194

207P Manchon égal, femelle NPTF

Laiton




C		F	L	Kg
NPTF1/8	207P-2	9/16	19	0,015
NPTF1/4	207P-4	3/4	28	0,041
NPTF3/8	207P-6	7/8	28	0,049
NPTF1/2	207P-8	1.1/16	38	0,089

* Dimensions de F en pouces

0164 Adaptateur, mâle NPT / femelle BSPP

Laiton




C1	C2		E	F	L	Kg
NPT1/8	G1/8	0164 11 10	7,5	14	20	0,015
NPT1/4	G1/4	0164 14 13	11	17	27,5	0,028
NPT3/8	G3/8	0164 18 17	11,5	22	28,5	0,044
NPT1/2	G1/2	0164 22 21	15	27	36,5	0,081
NPT3/4	G3/4	0164 28 27	16,5	32	38,5	0,110

Adaptateur pour piquage de coupleur automatique pour moules d'injection plastique.

0167 Adaptateur, mâle BSPT / femelle NPT

Laiton




C1	C2		F	L	Kg
R1/8	NPT1/8	0167 10 11	14	21	0,016
R1/4	NPT1/4	0167 13 14	17	28,5	0,029
R3/8	NPT3/8	0167 17 18	22	29,5	0,047
R1/2	NPT1/2	0167 21 22	27	37,5	0,088
R3/4	NPT3/4	0167 27 28	32	39,5	0,119

Adaptateur pour piquage de coupleur automatique pour moules d'injection plastique.

0168 Réduction, mâle BSPP / femelle BSPP et métrique

Laiton, polymère technique




C1	C2		E	F	H	Kg
G1/8	M5x0,8	0168 10 19	7	14	6	0,009
G1/4	M5x0,8	0168 13 19	7	17	7	0,017
	G1/8	0168 13 10	7	17	7	0,011
	G1/8	0168 17 10	9	19	6	0,019
G3/8	G1/4	0168 17 13	9	19	6	0,012
	G1/8	0168 21 10	11	24	10	0,052
G1/2	G1/4	0168 21 13	11	24	10	0,042
	G3/8	0168 21 17	11	24	10	0,030
	G1/4	0168 27 13	11	32	12	0,098
G3/4	G3/8	0168 27 17	11	32	12	0,084
	G1/2	0168 27 21	11	32	12	0,063

Vis avec rondelle-joint

0163 Réduction inégale, mâle BSPT / femelle BSPP

Laiton



C1	C2		F	L	Kg
R1/4	G1/8	0163 13 10	14	16	0,009
R3/8	G1/8	0163 17 10	17	16,5	0,020
	G1/4	0163 17 13	17	16,5	0,012
	G1/8	0163 21 10	22	21	0,048
R1/2	G1/4	0163 21 13	22	21	0,038
	G3/8	0163 21 17	22	21	0,025
	G1/4	0163 27 13	27	24	0,085
R3/4	G3/8	0163 27 17	27	24	0,069
	G1/2	0163 27 21	27	24	0,046
R1	G3/4	0163 34 27	36	27	0,085