

209P Réduction, mâle / femelle NPTF

Laiton



C	C1		F	L	Kg
NPTF1/4	NPTF1/8	209P-4-2	9/16	19	0,012
NPTF3/8	NPTF1/8	209P-6-2	11/16	18	0,024
	NPTF1/4	209P-6-4	11/16	19	0,179
NPTF1/2	NPTF1/8	209P-8-2	7/8	25	0,059
	NPTF1/4	209P-8-4	7/8	26	0,048
NPTF3/4	NPTF3/8	209P-8-6	7/8	26	0,033
	NPTF1/4	209P-12-4	1/2	25	0,093
NPTF1/2	NPTF3/8	209P-12-6	1/2	26	0,080
	NPTF1/2	209P-12-8	1/2	26	0,057

* Dimensions de F en pouces

0169 Grossisseur, mâle BSPP / femelle BSPP

Laiton, polymère technique




C1	C2		E1	E2	F	L	Kg
G1/8	G1/4	0169 10 13	5	11,0	17	16	0,019
	G3/8	0169 10 17	5	14,0	22	19,5	0,038
G1/4	G3/8	0169 13 17	7	14,0	22	19,5	0,041
	G1/2	0169 13 21	7	14,5	27	20,5	0,060
G3/8	G1/2	0169 17 21	8	14,5	27	20,5	0,062
	G3/4	0169 17 27	8	15,5	32	22	0,082
G1/2	G3/4	0169 21 27	9,5	15,5	32	22,5	0,087

Vis avec rondelle-joint

FG43 Grossisseur femelle BSPP / mâle BSPT


Laiton



C	C1		E	F	L	Kg
R1/8	G1/4	1/4X1/8FG43B	11	17	21,5	0,019
R1/8	G3/8	3/8X1/8FG43B	12	22	25	0,035
R1/4	G3/8	3/8X1/4FG43B	12	22	28	0,040
R1/2	G3/4	3/4X1/2FG43B	16	32	39	0,107

222P Réduction, femelle / mâle NPTF

Laiton



C	C1		F	L	Kg
NPTF1/8	NPTF1/4	222P-4-2	3/4	27	0,031
NPTF1/4	NPTF3/8	222P-6-4	7/8	32	0,046
NPTF3/8	NPTF1/2	222P-8-6	11/16	37	0,082

* Dimensions de F en pouces

0121 Mamelon égal et inégal, mâle BSPT


Laiton



C1	C2		F	L	Kg
R1/8	R1/8	0121 10 10	11	19	0,009
R1/4	R1/8	0121 13 10	14	23,5	0,017
	R1/4	0121 13 13	14	27	0,020
R3/8	R1/8	0121 17 10	17	24	0,021
	R1/4	0121 17 13	17	27,5	0,026
R1/2	R3/8	0121 17 17	17	28	0,026
	R1/8	0121 21 10	22	28,5	0,041
	R1/4	0121 21 13	22	32	0,045
	R3/8	0121 21 17	22	32,5	0,045
R3/4	R1/2	0121 21 21	22	36	0,052
	R1/4	0121 27 13	27	35	0,078
	R3/8	0121 27 17	27	35,5	0,077
	R1/2	0121 27 21	27	39	0,084
R1	R3/4	0121 27 27	27	40	0,090
	R3/8	0121 34 17	36	38,5	0,127
	R1/2	0121 34 21	36	42	0,135
	R3/4	0121 34 27	36	43	0,144
R1 1/4	R1	0121 34 34	36	46	0,152
	R1/2	0121 42 21	46	46,5	0,219
	R3/4	0121 42 27	46	47,5	0,229
	R1	0121 42 34	46	50,5	0,234
	R1 1/4	0121 42 42	46	53	0,230

FF44 Mamelon égal, mâle BSPP

Laiton



C		E	F	L	Kg
G1/8	1/8FF44B	6	14	19	0,018
G1/4	1/4FF44B	7	17	22	0,022
G3/8	3/8FF44B	8	22	24	0,040
G1/2	1/2FF44B	10	27	31	0,077

Raccords livrés avec deux joints cuivre