


0206 Bouchon à 6 pans creux, mâle BSPT

Acier




C		E1	E2 max	E2 min	F	G	H	Kg
R1/8	0206 10 00	4	3.9	2.1	5	9,7	8	0,003
R1/4	0206 13 00	5	5.8	3.2	7	13,2	10	0,007
R3/8	0206 17 00	5	5.8	3.2	8	16,7	10	0,012
R1/2	0206 21 00	5	6.8	3.2	10	21	10	0,022
R3/4	0206 27 00	6	7.8	4.2	12	26,4	12	0,048
R1	0206 34 00	6	9.3	4.7	17	33,2	12	0,085
R1 1/4	0206 42 00	11,5	9.8	5.2	22	41,9	18	0,166
R1 1/2	0206 49 00	11,5	9.8	5.2	24	47,8	20	0,222

Pour les bouchons BSPT, du 1/2" au 1 1/2" inclus :
Caractéristiques générales selon norme DIN 906.
Filetage, norme EN 10226-1

0206 Bouchon à 6 pans creux, mâle NPT


Acier



C		E1	E2 max	E2 min	F	G	H	Kg
NPT1/16	0206 08 00	6	6.4	3.8	4	7,8	7	0,002
NPT1/8	0206 11 00	6	5.0	3.2	5	10,2	8	0,003
NPT1/4	0206 14 00	8	7.2	4.4	6	13,6	10	0,007
NPT3/8	0206 18 00	8	7.5	4.7	8	17	11	0,012
NPT1/2	0206 22 00	8	9.9	6.3	10	21,2	13	0,023
NPT3/4	0206 28 00	11	10.4	6.8	14	26,6	17	0,048
NPT1	0206 35 00	13	12.4	8.0	17	33,2	19	0,082

0210 Bouchon à 6 pans, mâle BSPP et métrique

Acier




C		E	F	G	H	Kg
M8x1,25	0210 57 00	8	14	12	15	0,011
G1/8	0210 10 00	8	14	14	15	0,013
G1/4	0210 13 00	12	19	18	21	0,031
G3/8	0210 17 00	12	22	22	21	0,046
G1/2	0210 21 00	14	27	26	24	0,078
G3/4	0210 27 00	16	32	32	27	0,133
G1	0210 34 00	18	41	39	33	0,270

Profil de gorge suivant norme DIN 3852-1, forme D/E.
Filetage BSPP, norme ISO 228-1.
Filetage cylindrique métrique ISO, norme NFE 03-054

0216 Bouchon à 6 pans, mâle BSPT

Acier




C		F	H	Kg
R1/8	0216 10 00	13	16	0,012
R1/4	0216 13 00	17	19	0,023
R3/8	0216 17 00	19	21	0,038
R1/2	0216 21 00	22	23	0,060

Filetage BSPT, norme EN 10226-1

0216 Bouchon à 6 pans, mâle NPT

Acier



C		F	H	Kg
NPT1/8	0216 11 00	13	16	0,012
NPT1/4	0216 14 00	17	19	0,023
NPT1/2	0216 22 00	22	23	0,060