

Silencieux

0674 Silencieux polymère, mâle BSPP et métrique

	Polymère technique 	C		E	G	H	kg
		M5x0,8	0674 00 19	4	6,5	23	0,003
		G1/8	0674 00 10	6	12,5	34	0,002
		G1/4	0674 00 13	7	15,5	42,5	0,003
		G3/8	0674 00 17	11,5	18,5	67,5	0,007
		G1/2	0674 00 21	11	23,5	78	0,010
		G3/4	0674 00 27	15,5	38,5	131	0,035
		G1	0674 00 34	19,5	49	160	0,056

0676 Silencieux polymère réglé, mâle BSPP et métrique

	Polymère technique 	C		F	F1	G	H	H1	kg
		M5x0,8	0676 00 19	8	1,5	9,2	16	11	0,008
		G1/8	0676 00 10	13	2,5	15	20,5	14,5	0,003
		G1/4	0676 00 13	15	4	18	29	22	0,007
		G3/8	0676 00 17	20	6	24	38	30	0,018
		G1/2	0676 00 21	25	8	30	50	40	0,045

0670 Silencieux, mâle BSPP

	Bronze fritté, laiton 	C		G	J	L	L1	kg
		G1/8	0670 00 10	12	7	22	17	0,007
		G1/4	0670 00 13	15	9	27	21	0,015
		G3/8	0670 00 17	19	11	35	28	0,028
		G1/2	0670 00 21	23	13	43	34	0,049
		G3/4	0670 00 27	30	17	55	45	0,091
		G1	0670 00 34	37	21	65	53	0,152

0673 Silencieux compact, mâle BSPP et métrique

	Bronze fritté, laiton 	C		E	F	H	kg
		M5x0,8	0673 00 19	4	7	8	0,001
		G1/8	0673 00 10	8	14	14	0,008
		G1/4	0673 00 13	8	17	14	0,012
		G3/8	0673 00 17	10	22	18	0,020
		G1/2	0673 00 21	12	27	21	0,042

0675 Silencieux à embase, mâle BSPP et métrique

	Bronze fritté, laiton 	C		F	L	L1	kg
		M5x0,8	0675 00 19	7	16	12	0,002
		M7x1	0675 00 55	11	25	19	0,005
		G1/8	0675 00 10	14	42	34	0,014
		G1/4	0675 00 13	17	52	44	0,022
		G3/8	0675 00 17	22	54	44	0,037
		G1/2	0675 00 21	27	65	53	0,072