


0917 Té égal en bout, mâle BSPT / femelle BSPP


Laiton nickelé



C1	C2		E	G	H	H1	J	L	Kg
R1/8	G1/8	0917 00 10	8	13	17	18,5	10	18,5	0,019
R1/4	G1/4	0917 00 13	11	17	22,5	22,5	12	22,5	0,038
R3/8	G3/8	0917 00 17	11,5	21	25,5	25,5	15	25,5	0,058
R1/2	G1/2	0917 00 21	14	26	30	30	19	30	0,089
R3/4	G3/4	0917 00 27	16,5	32	34,5	35,5	22	35,5	0,136

0927 Té égal, mâle BSPT


Laiton nickelé



C		H	J	L	Kg
R1/8	0927 00 10	17	10	34	0,013
R1/4	0927 00 13	22,5	12	45	0,032
R3/8	0927 00 17	25,5	15	51	0,056
R1/2	0927 00 21	30	19	60	0,079
R3/4	0927 00 27	34,5	22	69	0,130

0928 Té égal au centre, mâle BSPT / femelle BSPP


Laiton nickelé



C1	C2		E	H	J	L	Kg
R1/8	G1/8	0928 00 10	8	34	10	18,5	0,016
R1/4	G1/4	0928 00 13	11	45	12	22,5	0,035
R3/8	G3/8	0928 00 17	11,5	51	15	25,5	0,053
R1/2	G1/2	0928 00 21	14	60	19	30	0,086
R3/4	G3/4	0928 00 27	16,5	69	22	35,5	0,236

0932 Té égal en bout, mâle BSPT / femelle BSPP


Laiton nickelé



C1	C2		E	H	H1	J	L	Kg
R1/8	G1/8	0932 00 10	8	17	18,5	10	17	0,016
R1/4	G1/4	0932 00 13	11	22,5	22,5	12	22,5	0,035
R3/8	G3/8	0932 00 17	11,5	25,5	25,5	15	25,5	0,053
R1/2	G1/2	0932 00 21	14	30	30	19	30	0,091
R3/4	G3/4	0932 00 27	16,5	34,5	35,5	22	34,5	0,080

0908 Croix égale, femelle BSPP


Laiton nickelé



C		E	G	H	J	Kg
G1/8	0908 00 10	8	13	21	10	0,038
G1/4	0908 00 13	11	17	25,5	13	0,074
G3/8	0908 00 17	11,5	21	28	17	0,109
G1/2	0908 00 21	14	26	33,5	21	0,186

0909 Croix égale au centre, mâle BSPT / femelle BSPP


Laiton nickelé



C1	C2		E	G	H	J	Kg
R1/8	G1/8	0909 00 10	8	13	18,5	10	0,034
R1/4	G1/4	0909 00 13	11	17	23,5	13	0,069
R3/8	G3/8	0909 00 17	11,5	21	26	17	0,098
R1/2	G1/2	0909 00 21	14	26	31	21	0,168

0178 Réduction, mâle BSPP et métrique / femelle BSPP et métrique

Laiton nickelé, NBR




C1	C2		E	F	L	Kg
M7x1	M5x0,8	0178 55 19	5	10	12	0,005
G1/8	M5x0,8	0178 10 19	5	13	9	0,005
G1/4	G1/8	0178 13 10	5,5	16	9,5	0,006
G3/8	G1/8	0178 17 10	5,5	20	10,5	0,016
G3/8	G1/4	0178 17 13	5,5	20	10,5	0,011
G1/2	G1/4	0178 21 13	7,5	24	12,5	0,024
G1/2	G3/8	0178 21 17	7,5	24	12,5	0,016
G3/4	G1/2	0178 27 21	7,5	32	13,5	0,035

Avec joint d'étanchéité

0903 Réduction à visser, mâle BSPP / femelle BSPP

Laiton nickelé



C1	C2		E	F	Kg
G1/4	G1/8	0903 10 13	8	6	0,004
G3/8	G1/4	0903 13 17	9	8	0,007
G1/2	G3/8	0903 17 21	10	10	0,011
G3/4	G1/2	0903 21 27	14	12	0,023
G1	G3/4	0903 27 34	20	17	0,038