

0904 Réduction, mâle BSPT / femelle BSPP


Laiton nickelé



C1	C2		F	L	Kg
R1/4	G1/8	0904 10 13	14	16	0,010
R3/8	G1/8	0904 10 17	17	16,5	0,020
R1/2	G1/8	0904 10 21	22	19,5	0,035
R3/8	G1/4	0904 13 17	17	16,5	0,015
R1/2	G1/4	0904 13 21	22	19,5	0,031
R1/2	G3/8	0904 17 21	22	19,5	0,024
R3/4	G3/8	0904 17 27	27	23	0,056
R3/4	G1/2	0904 21 27	27	23	0,045
R1	G1/2	0904 21 34	34	27	0,101
R1	G3/4	0904 27 34	34	27	0,074

0905 Réduction, mâle BSPP / femelle BSPP et métrique

Laiton nickelé




C1	C2		E	F	L	Kg
G1/8	M5x0,8	0905 19 10	6	14	4,5	0,008
G1/4	G1/8	0905 10 13	8	17	5	0,011
G3/8	G1/8	0905 10 17	9	19	5	0,019
	G1/4	0905 13 17	9	19	5	0,013
G1/2	G1/4	0905 13 21	10	24	5,5	0,031
	G3/8	0905 17 21	10	24	5,5	0,022
G3/4	G3/8	0905 17 27	11	30	6,5	0,055
	G1/2	0905 21 27	11	30	6,5	0,041

* Pour les schémas détaillés du filetage intérieur, merci de nous consulter.

0906 Grossisseur, mâle BSPP et métrique / femelle BSPP


Laiton nickelé



C1	C2		E1	E2	F	L	Kg
M5x0,8	G1/8	0906 10 19	4	8.0	14	10,5	0,010
	G1/8	0906 00 10	6	8.0	14	10,5	0,011
G1/8	G1/4	0906 10 13	6	11.0	17	13,5	0,017
	G3/8	0906 10 17	6	11.5	22	14,5	0,029
G1/4	G1/4	0906 00 13	8	11.0	17	13,5	0,019
	G3/8	0906 13 17	8	11.5	22	14,5	0,032
G1/2	G1/2	0906 13 21	8	14.0	24	18	0,037
	G3/8	0906 00 17	9	11.5	22	14,5	0,035
G3/8	G1/2	0906 17 21	9	14.0	24	18	0,038
	G1/2	0906 00 21	10	14.0	26	20	0,053

0933 Grossisseur, mâle BSPT / femelle BSPP

Laiton nickelé



C1	C2		F	L	Kg
R1/8	G1/8	0933 00 10	14	10	0,011
R1/4	G1/4	0933 00 13	17	13,5	0,020
R3/8	G3/8	0933 00 17	22	14,5	0,037
R1/2	G1/2	0933 00 21	26	18	0,058
R1/8	G1/4	0933 10 13	17	13,5	0,017
R1/4	G3/8	0933 13 17	22	14,5	0,034
R1/4	G1/2	0933 13 21	24	18	0,038
R3/8	G1/2	0933 17 21	24	18	0,041
R1/2	G3/4	0933 21 27	32	23,5	0,080

0907 Prolongateur égal, mâle BSPP / femelle BSPP


Laiton nickelé



C		E	F	L	Kg
G1/8	0907 00 10	6	14	16	0,015
	0907 00 10 01	6	14	36	0,030
	0907 00 13	8	17	27	0,031
G1/4	0907 00 13 01	8	17	43	0,047

0920 Traversée de cloison égale, femelle BSPP et métrique

Laiton nickelé



C	C1		F	F1	K max	L	L1	ØT	Kg
M5x0,8	M10x1	0920 00 19	14	14	7.0	10,5	3,5	10,5	0,012
G1/8	M16x1.5	0920 00 10	19	22	10.0	14	4	16,5	0,030
G1/4	M20x1.5	0920 00 13	24	27	16.0	21	4	20,5	0,057
G3/8	M26x1.5	0920 00 17	30	32	15.0	21	5	26,5	0,096
G1/2	M28x1.5	0920 00 21	32	36	21.0	27	6	28,5	0,115