


0222 Bouchon à 6 pans, creux mâle BSPP et métrique

Laiton nickelé, NBR




C		E	F	F1	H	Kg
M5x0,8	0222 19 00	3,5	8	2,5	7	0,002
M7x1	0222 55 00	5	10	3	8,5	0,003
G1/8	0222 10 00	5	13	5	8,5	0,006
G1/4	0222 13 00	5,5	16	6	9,5	0,010
G3/8	0222 17 00	5,5	20	8	10,5	0,019
G1/2	0222 21 00	7,5	24	10	12	0,031

Avec joint d'étanchéité

0936 Bouchon à 6 pans creux, mâle BSPT


Laiton nickelé



C		F	H	Kg
R1/8	0936 00 10	5	8	0,003
R1/4	0936 00 13	6	10	0,007
R3/8	0936 00 17	8	11	0,013
R1/2	0936 00 21	10	13	0,026

0919 Bouchon à 6 pans creux, mâle BSPP et métrique


Laiton nickelé



C		E	F	G	H	Kg
M5x0,8	0919 00 19	4	2,5	8	6,5	0,001
G1/8	0919 00 10	6	5	15	9,5	0,007
G1/4	0919 00 13	8	6	18	11,5	0,013
G3/8	0919 00 17	9	8	21	13	0,021
G1/2	0919 00 21	10	10	25	14,5	0,035
G3/4	0919 00 27	11	14	31	15,5	0,049
G1	0919 00 34	13	17	38	17,5	0,072

0919..1 Bouchon à 6 pans creux avec joint, mâle BSPP et métrique

Laiton nickelé



C		E	F	G	H	Kg
G1/8	0919 01 10	6,5	5	14	9,5	0,005
G1/4	0919 01 13	8	6	17	11,5	0,011
G3/8	0919 01 17	9	8	20	12,5	0,018
M5X0,8	0919 01 19	4,5	2,5	8	7,2	0,001
G1/2	0919 01 21	10	10	26	14	0,032