


1805 Piquage droit, mâle BSPT


Acier inox 316L



ØD	C		F	F1	H max	H1	Kg
6	R1/8	1805 06 10	12	13	19,5	7,5	0,017
	R1/4	1805 06 13	14	13	19,5	7,5	0,025
8	R1/8	1805 08 10	13	14	21	7	0,019
	R1/4	1805 08 13	14	14	21	7	0,024
10	R1/4	1805 10 13	17	19	25,5	9	0,043
	R3/8	1805 10 17	17	19	25,5	9	0,049
12	R1/2	1805 10 21	22	19	26,5	10	0,076
	R1/4	1805 12 13	19	22	26	9	0,054
16	R3/8	1805 12 17	19	22	26	9	0,057
	R1/2	1805 12 21	22	22	27	10	0,081
16	R3/8	1805 16 17	24	27	28,5	9,5	0,086
	R1/2	1805 16 21	24	27	28,5	9,5	0,093

1809 Équerre, mâle BSPT


Acier inox 316L



ØD	C		F	H	J	L max	L1	Kg
6	R1/8	1809 06 10	13	18	8	25,5	13,5	0,020
	R1/4	1809 06 13	13	23	10	25,5	13,5	0,029
8	R1/8	1809 08 10	14	20,5	10	28,5	14,5	0,026
	R1/4	1809 08 13	14	23	10	28,5	14,5	0,030
10	R1/4	1809 10 13	19	25	12	32,5	16	0,051
	R3/8	1809 10 17	19	25,5	12	32,5	16	0,057
12	R1/2	1809 10 21	19	32	18	36,5	20	0,091
	R1/4	1809 12 13	22	26	14	34	17	0,067
16	R3/8	1809 12 17	22	27	14	34	17	0,070
	R1/2	1809 12 21	22	32	18	37	20	0,098
16	R3/8	1809 16 17	27	28,5	18	39,5	21	0,107
	R1/2	1809 16 21	27	31,5	18	39,5	21	0,114

1805 Piquage droit, mâle NPT


Acier inox 316L



ØD	C		F	F1	H max	H1	Kg
6	NPT1/8	1805 06 11	12	13	19,5	7,5	0,018
	NPT1/4	1805 06 14	14	13	19,5	7,5	0,027
	NPT3/8	1805 06 18	19	13	20,5	8,5	0,033
8	NPT1/8	1805 08 11	13	14	21	7	0,021
	NPT1/4	1805 08 14	14	14	21	7	0,027
10	NPT1/4	1805 10 14	17	19	25,5	9	0,045
	NPT3/8	1805 10 18	19	19	25,5	9	0,055
	NPT1/2	1805 10 22	22	19	26,5	10	0,082
12	NPT1/4	1805 12 14	19	22	26	9	0,057
	NPT3/8	1805 12 18	19	22	26	9	0,060
	NPT1/2	1805 12 22	22	22	27	10	0,086

1809 Équerre, mâle NPT


Acier inox 316L



ØD	C		F	H	J	L max	L1	Kg
6	NPT1/4	1809 06 14	13	25,5	10	25,5	13,5	0,032
8	NPT1/8	1809 08 11	14	22	10	28,5	14,5	0,027
	NPT1/4	1809 08 14	14	25,5	10	28,5	14,5	0,032
10	NPT1/4	1809 10 14	19	27,5	12	32,5	16	0,053
	NPT3/8	1809 10 18	19	28	12	32,5	16	0,060
12	NPT1/2	1809 10 22	19	35	18	36,5	20	0,096
	NPT1/2	1809 12 22	22	35	18	37	20	0,101

1814 Piquage droit, femelle BSPP

Acier inox 316L



ØD	C		E	F	F1	H max	H1	Kg
6	G1/8	1814 06 10	7,5	14	13	29	17	0,024
	G1/4	1814 06 13	11	17	13	29	21	0,031
8	G1/4	1814 08 13	11	17	14	34,5	20,5	0,033
10	G3/8	1814 10 17	11,5	22	19	38,5	22	0,064
	G1/2	1814 10 21	15	27	19	43	26,5	0,094
12	G3/8	1814 12 17	11,5	22	22	39	22	0,073
	G1/2	1814 12 21	15	27	22	43,5	26,5	0,102
16	G1/2	1814 16 21	15	27	27	45	26	0,121