


1820 Adaptateur d'orientation, mâle BSPT


Acier inox 316L



ØD	C		F	L	L1	Kg
6	R1/8	1820 06 10	12	26,5	15	0,009
	R1/4	1820 06 13	14	31	15	0,017
8	R1/8	1820 08 10	12	28,5	17	0,008
	R1/4	1820 08 13	14	33	17	0,016
10	R1/4	1820 10 13	14	36	20	0,016
	R3/8	1820 10 17	17	36,5	20	0,025
12	R1/2	1820 10 21	22	41	20	0,052
	R1/4	1820 12 13	14	36	20	0,016
12	R3/8	1820 12 17	17	36,5	20	0,023
	R1/2	1820 12 21	22	41	20	0,048
16	R3/8	1820 16 17	17	39,5	23	0,022
	R1/2	1820 16 21	22	44	23	0,039

1820 Adaptateur d'orientation, mâle NPT

Acier inox 316L



ØD	C		F	L	L1	Kg
8	NPT1/8	1820 08 11	12	28,5	17	0,009
	NPT1/4	1820 08 14	14	33	17	0,019
10	NPT1/4	1820 10 14	14	36	20	0,018
	NPT1/4	1820 12 14	14	36	20	0,019
12	NPT3/8	1820 12 18	19	36,5	20	0,028
	NPT1/2	1820 12 22	22	41	20	0,053