

Adaptateurs en acier inoxydable

1862 Manchon de réduction, femelle BSPP


Acier inox 316L



C1	C2		F	L	Kg
G1/4	G1/8	1862 13 10	17	20,5	0,024
G3/8	G1/8	1862 17 10	22	21	0,043
	G1/4	1862 17 13	22	24,5	0,048
G1/2	G1/4	1862 21 13	27	28,5	0,086
	G3/8	1862 21 17	27	29	0,081
G3/4	G1/2	1862 27 21	32	39,5	0,148
G1	G3/4	1862 34 27	41	45	0,282

1864 Adaptateur, mâle NPT / femelle BSPP


Acier inox 316L



C1	C2		E	F	L	Kg
NPT1/8	G1/8	1864 11 10	7,5	14	21,5	0,015
NPT1/4	G1/4	1864 14 13	11	17	30	0,028
NPT3/8	G3/8	1864 18 17	11,5	22	31	0,044
NPT1/2	G1/2	1864 22 21	15	27	39,5	0,081

1867 Adaptateur, mâle BSPT / femelle NPT

Acier inox 316L



C1	C2		E	F	L	Kg
R1/8	NPT1/8	1867 10 11	8	14	21	0,015
R1/4	NPT1/4	1867 13 14	11,5	17	28,5	0,028
R3/8	NPT3/8	1867 17 18	12	22	29,5	0,045
R1/2	NPT1/2	1867 21 22	15,5	27	37,5	0,082

1863 Réduction, mâle BSPT / femelle BSPP

Acier inox 316L



C1	C2		F	L	Kg
R1/4	G1/8	1863 13 10	14	16	0,008
R3/8	G1/8	1863 17 10	17	16,5	0,019
	G1/4	1863 17 13	17	16,5	0,011
R1/2	G1/4	1863 21 13	22	21	0,035
	G3/8	1863 21 17	22	21	0,023
R3/4	G1/2	1863 27 21	27	25,5	0,045
R1	G3/4	1863 34 27	36	28,5	0,084

1872 Réduction, mâle NPT / femelle NPT


Acier inox 316L



C1	C2		F	L	Kg
NPT1/4	NPT1/8	1872 14 11	14	16	0,010
NPT3/8	NPT1/8	1872 18 11	19	16,5	0,023
	NPT1/4	1872 18 14	19	16,5	0,016
NPT1/2	NPT1/4	1872 22 14	22	21	0,039
	NPT3/8	1872 22 18	22	21	0,027

1861 Grossisseur, mâle BSPT / femelle BSPP

Acier inox 316L



C1	C2		E	F	L	Kg
R1/8	G1/4	1861 10 13	11	17	24	0,022
	G3/8	1861 10 17	11,5	22	25	0,038
R1/4	G3/8	1861 13 17	11,5	22	28,5	0,042
	G1/2	1861 13 21	15	27	32,5	0,069
R3/8	G1/2	1861 17 21	15	27	33	0,069
R1/2	G3/4	1861 21 27	16,5	32	38	0,093
R3/4	G1	1861 27 34	19	41	43,5	0,181