


1873 Grossisseur, mâle NPT / femelle NPT

Acier inox 316L



C1	C2		E	F	L	Kg
NPT1/8	NPT1/4	1873 11 14	14	17	25	0,024
	NPT3/8	1873 11 18	14	22	25	0,039
NPT1/4	NPT3/8	1873 14 18	14	22	28,5	0,043
	NPT1/2	1873 14 22	17,5	27	31	0,066
NPT3/8	NPT1/2	1873 18 22	17,5	27	31,5	0,066

1821 Mamelon égal et inégal, mâle BSPT

Acier inox 316L



C1	C2		F	L	Kg
R1/8	R1/8	1821 10 10	12	19	0,009
	R1/8	1821 13 10	14	23,5	0,015
R1/4	R1/4	1821 13 13	14	27	0,019
	R1/4	1821 17 13	17	27,5	0,023
R3/8	R3/8	1821 17 17	17	28	0,024
	R3/8	1821 21 17	22	32,5	0,042
R1/2	R1/2	1821 21 21	22	36	0,049
	R1/2	1821 27 21	27	41	0,079
R3/4	R3/4	1821 27 27	27	42	0,088
	R3/4	1821 34 27	36	46	0,141
R1	R1	1821 34 34	36	48	0,147

1821 Mamelon égal, mâle NPT


Acier inox 316L



C		F	L	Kg
NPT1/8	1821 11 11	12	23	0,011
NPT1/4	1821 14 14	14	32	0,023
NPT3/8	1821 18 18	19	33	0,031
NPT1/2	1821 22 22	22	42	0,056
NPT3/4	1821 28 28	27	40	0,083

1823 Douille annelée pour tuyau caoutchouc, mâle BSPT


Acier inox 316L



ØD	ØD1	C		F	L	L1	ØT	Kg
7	9	R1/8	1823 07 10	10	34	22,5	5	0,009
	9	R1/4	1823 07 13	14	38,5	22,5	6	0,017
10	12,2	R1/4	1823 10 13	14	38,5	22,5	7	0,018
	12,2	R3/8	1823 10 17	17	39	22,5	9,5	0,021
13	15	R3/8	1823 13 17	17	46	29,5	11	0,025
16	18,5	R1/2	1823 16 21	22	59	38	14	0,048

1823 Douille annelée pour tuyau caoutchouc, mâle NPT

Acier inox 316L



ØD	ØD1	C		F	L	L1	ØT	Kg
1/4	8,3	NPT1/8	1823 56 11	12	34	22,5	5,3	0,010
	8,3	NPT1/4	1823 56 14	14	38,5	22,5	5,3	0,016
3/8	11,7	NPT1/4	1823 60 14	14	38,5	22,5	8,5	0,018
	11,7	NPT3/8	1823 60 18	19	39	22,5	8,5	0,026