


3144 Y double égal et inégal


Polymère technique, NBR



ØD	ØD1		K	K1	L	N	N1	ØT	Kg
4	4	3144 04 04	25,5	21	30,5	10	8,5	3,7	0,015
	6	3144 04 06	25,5	21	30,5	10	8,5	3,7	0,013
6	6	3144 06 06	31,5	26,5	37,5	12	10	3,7	0,032
	8	3144 06 08	31,5	26,5	38	12	10	3,7	0,026

3304 Multi-té d'alimentation


Polymère technique, NBR



ØD1	ØD2		H	L	L/2	N	ØT	Kg
6	4	3304 06 04	24,5	34	37	11,5	4,2	0,015
	4	3304 08 04	24,5	34	37	11,5	4,2	0,012
8	6	3304 08 06	24,5	34	37	11,5	4,2	0,010
	6	3304 10 06	36	44	40,5	14,5	4,2	0,019
10	8	3304 10 08	36	44	40,5	15,5	4,2	0,015

3306 Multi-té d'alimentation à 90°


Polymère technique, NBR



ØD1	ØD2		G	G1	H	L/2	N	N1	ØT	Kg
6	4	3306 06 04	13,5	11	18,5	36	43	11,5	4,2	0,034
8	4	3306 08 04	13,5	11	18,5	36,5	43	11,5	4,2	0,025
	6	3306 08 06	13,5	11	18,5	36,5	43	11,5	4,2	0,022
10	6	3306 10 06	16	13,5	23	42	52	14,5	4,2	0,048
	8	3306 10 08	16	13,5	23,5	42	52	14,5	4,2	0,021

3310 Nourrice de distribution en ligne

Aluminium traité, NBR



ØD	C		Nombre de sorties	E	H	K	L	L1	N	Kg
4	G1/4	3310 04 13	8	10	33	20	114	104	11,5	0,164
6	G1/4	3310 06 13	8	10	33	20	114	104	12,5	0,160
8	G3/8	3310 08 17	6	12	33	20	114	104	15	0,149
10	G1/2	3310 10 21	6	16	48	25	145,5	135,5	17	0,329
12	G1/2	3310 12 21	4	16	45	25	158	148	20,5	0,354

Parker Legris propose le modèle adapté à chaque configuration d'installation.

