


3160 Auto-obturant encliquetable


Polymère technique, NBR



ØD		L	L1	Kg
4	3160 04 00	46	33,5	0,006
6	3160 06 00	53,5	31	0,009
8	3160 08 00	58	31	0,014

3159 Équerre oscillante, mâle BSPT

Polymère technique, laiton nickelé, NBR




ØD	C		F	G	H	L	Kg
4	R1/8	3159 04 10	12	11	22	17,5	0,013
6	R1/8	3159 06 10	14	14	26,5	20,5	0,020
	R1/4	3159 06 13	14	14	23,5	20,5	0,022
8	R1/8	3159 08 10	17	16	32	23,5	0,034
	R1/4	3159 08 13	17	16	29	23,5	0,034
10	R3/8	3159 08 17	17	16	25	23,5	0,031
	R1/4	3159 10 13	19	19,5	37,5	29	0,051
12	R3/8	3159 10 17	19	19,5	33,5	29	0,046
	R1/4	3159 12 13	21	22	44,5	33,5	0,074
12	R3/8	3159 12 17	21	22	41	33,5	0,068

Filetage avec pré-coating

3189 Équerre oscillante, mâle BSPP et métrique

Polymère technique, laiton nickelé, NBR



ØD	C		E	F	G	H	L	Kg
4	M5x0,8	3189 04 19	3	12	11	24,5	17,5	0,012
	G1/8	3189 04 10	5	13	11	23	17,5	0,014
6	M5x0,8	3189 06 19	3	12	14	27,5	20,5	0,017
	G1/8	3189 06 10	5	14	14	27	20,5	0,019
8	G1/4	3189 06 13	5,5	16	14	25,5	20,5	0,023
	G1/8	3189 08 10	5	17	16	33,5	23,5	0,034
10	G1/4	3189 08 13	5,5	17	16	31	23,5	0,032
	G3/8	3189 08 17	5,5	20	16	29,5	23,5	0,039
12	G1/4	3189 10 13	5,5	19	19,5	39	29	0,053
	G3/8	3189 10 17	5,5	20	19,5	37	29	0,051
12	G1/4	3189 12 13	5,5	21	22	46,5	33,5	0,073
	G3/8	3189 12 17	5,5	21	22	45,5	33,5	0,071