


3144 Y double égal et inégal


Polymère technique, NBR



| ØD | ØD1 |                            | K    | K1   | L    | N  | N1  | ØT  | Kg    |
|----|-----|----------------------------|------|------|------|----|-----|-----|-------|
| 4  | 4   | <a href="#">3144 04 04</a> | 25,5 | 21   | 30,5 | 10 | 8,5 | 3,7 | 0,015 |
|    | 6   | <a href="#">3144 04 06</a> | 25,5 | 21   | 30,5 | 10 | 8,5 | 3,7 | 0,013 |
| 6  | 6   | <a href="#">3144 06 06</a> | 31,5 | 26,5 | 37,5 | 12 | 10  | 3,7 | 0,032 |
|    | 8   | <a href="#">3144 06 08</a> | 31,5 | 26,5 | 38   | 12 | 10  | 3,7 | 0,026 |

3304 Multi-té d'alimentation


Polymère technique, NBR



| ØD1 | ØD2 |                            | H    | L  | L/2  | N    | ØT  | Kg    |
|-----|-----|----------------------------|------|----|------|------|-----|-------|
| 6   | 4   | <a href="#">3304 06 04</a> | 24,5 | 34 | 37   | 11,5 | 4,2 | 0,015 |
| 8   | 4   | <a href="#">3304 08 04</a> | 24,5 | 34 | 37   | 11,5 | 4,2 | 0,012 |
|     | 6   | <a href="#">3304 08 06</a> | 24,5 | 34 | 37   | 11,5 | 4,2 | 0,010 |
| 10  | 6   | <a href="#">3304 10 06</a> | 36   | 44 | 40,5 | 14,5 | 4,2 | 0,019 |
|     | 8   | <a href="#">3304 10 08</a> | 36   | 44 | 40,5 | 15,5 | 4,2 | 0,015 |

3306 Multi-té d'alimentation à 90°


Polymère technique, NBR



| ØD1 | ØD2 |                            | G    | G1   | H    | L/2  | N  | N1   | ØT  | Kg    |
|-----|-----|----------------------------|------|------|------|------|----|------|-----|-------|
| 6   | 4   | <a href="#">3306 06 04</a> | 13,5 | 11   | 18,5 | 36   | 43 | 11,5 | 4,2 | 0,034 |
| 8   | 4   | <a href="#">3306 08 04</a> | 13,5 | 11   | 18,5 | 36,5 | 43 | 11,5 | 4,2 | 0,025 |
|     | 6   | <a href="#">3306 08 06</a> | 13,5 | 11   | 18,5 | 36,5 | 43 | 11,5 | 4,2 | 0,022 |
| 10  | 6   | <a href="#">3306 10 06</a> | 16   | 13,5 | 23   | 42   | 52 | 14,5 | 4,2 | 0,048 |
|     | 8   | <a href="#">3306 10 08</a> | 16   | 13,5 | 23,5 | 42   | 52 | 14,5 | 4,2 | 0,021 |

3310 Nourrice de distribution en ligne

Aluminium traité, NBR



| ØD | C    |                            | Nombre de sorties | E  | H  | K  | L     | L1    | N    | Kg    |
|----|------|----------------------------|-------------------|----|----|----|-------|-------|------|-------|
| 4  | G1/4 | <a href="#">3310 04 13</a> | 8                 | 10 | 33 | 20 | 114   | 104   | 11,5 | 0,164 |
| 6  | G1/4 | <a href="#">3310 06 13</a> | 8                 | 10 | 33 | 20 | 114   | 104   | 12,5 | 0,160 |
| 8  | G3/8 | <a href="#">3310 08 17</a> | 6                 | 12 | 33 | 20 | 114   | 104   | 15   | 0,149 |
| 10 | G1/2 | <a href="#">3310 10 21</a> | 6                 | 16 | 48 | 25 | 145,5 | 135,5 | 17   | 0,329 |
| 12 | G1/2 | <a href="#">3310 12 21</a> | 4                 | 16 | 45 | 25 | 158   | 148   | 20,5 | 0,354 |

Parker Legris propose le modèle adapté à chaque configuration d'installation.

