


0135 Connecteur de distribution, femelle BSPP

Laiton




C		H	H1	K	L	N	Kg
G1/4	0135 06 13	30	13	25	70	37	0,335
	0135 09 13	30	13	25	87	54	0,409
G1/2	0135 06 21	40	16	35	86	45	0,714
	0135 09 21	40	16	35	109	68	0,900
G3/4	0135 10 27	45	21	40	122	78	1,232

Cette pièce permet la distribution dans de nombreuses directions.

3311 Nourrice de distribution, femelle BSPP et métrique


Aluminium traité



C1	C2		Nbre de sorties	H	H1	H2	K	L	L1	N	ØT	Kg
G1/8	M5x0,8	3311 19 10 07	7	3,5	20	8,5	15	95	80	11	4,4	0,057
		3311 10 13 02	2	4,5	30	15	20	61	50	30	5	0,075
		3311 10 13 03	3	4,5	30	15	20	91	30	30	5	0,112
G1/4	G1/8	3311 10 13 04	4	4,5	30	15	20	121	60	30	5	0,165
		3311 10 13 05	5	4,5	30	15	20	151	90	30	5	0,209
		3311 10 13 06	6	4,5	30	15	20	181	120	30	5	0,244
G1/4		3311 13 17 02	2	5,5	30	11	20	74	61	36	6,5	0,076
		3311 13 17 03	3	6	30	11	20	110	36	36	6,5	0,121
G3/8	G1/4	3311 13 17 04	4	6	30	11	20	146	72	36	6,5	0,147
		3311 13 17 05	5	6	30	11	20	182	108	36	6,5	0,212
		3311 13 17 06	6	6	30	11	20	218	144	36	6,5	0,220

3312 Nourrice de distribution en croix, femelle BSPP et métrique


Aluminium traité



C		H	K	L	L1	N	ØT	Kg
M5x0,8	3312 00 19	20	10	20	12	12	4,5	0,008
G1/8	3312 00 10	30	16	30	23	22	4,5	0,028
G1/4	3312 00 13	40	20	40	30	27	5,5	0,061
G3/8	3312 00 17	50	25	50	38	39	6,5	0,118
G1/2	3312 00 21	50	25	50	38	39	6,5	0,101

3313 Nourrice de distribution double, femelle BSPP


Aluminium traité



C1	C2		Nbre de sorties	H	H1	H2	K	L	L1	N	ØT	Kg
G1/4	G1/8	3313 10 13 02	2x2	4,5	30	15	20	61	50	30	5	0,075
	G1/8	3313 10 13 03	2x3	4,5	30	15	20	91	30	30	5	0,115
	G1/8	3313 10 13 04	2x4	4,5	30	15	20	121	60	30	5	0,151
	G1/8	3313 10 13 05	2x5	4,5	30	15	20	151	90	30	5	0,182
G3/8	G1/4	3313 13 17 02	2x2	6	40	20	20	74	61	36	6,5	0,109
	G1/4	3313 13 17 03	2x3	6	40	20	20	110	36	36	6,5	0,179
	G1/4	3313 13 17 04	2x4	6	40	20	20	146	72	36	6,5	0,238
	G1/4	3313 13 17 05	2x5	6	40	20	20	182	108	36	6,5	0,286
G1/2	G1/4	3313 13 21 03	2x3	6	40	20	28	116	36	36	6,5	0,230
	G1/4	3313 13 21 04	2x4	6	40	20	28	152	72	36	6,5	0,298
	G1/4	3313 13 21 05	2x5	6	40	20	28	188	108	36	6,5	0,377

3301 Nourrice de distribution modulaire

Aluminium traité, NBR




ØD		Nbre de sorties	H	H1	H2	H3	L	L1	N	N1	Kg
4	3301 04 00	8	25	10	4,5	16	73,5	25	35	17	0,108
6	3301 06 00	4	25	10	4,5	16	73,5	25	35	17	0,109

Fixation par vis M3 x 20

3303 Bouchon d'extrémité pour nourrice

Aluminium traité



	H	H1	L	Kg
3303 00 01	9,5	3,5	25	0,014