

LF3600 : Raccords instantanés en laiton nickelé chimique

de -20°C à +150°C
30 bar max.

3698 Té à piquage mâle au centre, BSP cylindrique et métrique



ØD	C	Référence
4	M5 x 0.8	3698 04 19
4	G1/8	3698 04 10
6	G1/8	3698 06 10
6	G1/4	3698 06 13
8	G1/8	3698 08 10
8	G1/4	3698 08 13
10	G1/4	3698 10 13
12	G3/8	3698 12 17
14	G1/2	3698 14 21

3606 Union double égale



ØD	Référence
4	3606 04 00
6	3606 06 00
8	3606 08 00
10	3606 10 00
12	3606 12 00
14	3606 14 00

3693 Té à piquage mâle en bout, BSP cylindrique et métrique



ØD	C	Référence
4	M5 x 0,8	3693 04 19
4	G1/8	3693 04 10
6	G1/8	3693 06 10
6	G1/4	3693 06 13
8	G1/8	3693 08 10
8	G1/4	3693 08 13
10	G1/4	3693 10 13
12	G3/8	3693 12 17
14	G1/2	3693 14 21

3616 Union double égale, traversée de cloison



ØD	Référence
4	3616 04 00
6	3616 06 00
8	3616 08 00
10	3616 10 00
12	3616 12 00
14	3616 14 00

3636 Union à piquage femelle, traversée de cloison, BSP cylindrique



ØD	C	Référence
4	G1/8	3636 04 10
6	G1/8	3636 06 10
6	G1/4	3636 06 13
8	G1/8	3636 08 10
8	G1/4	3636 08 13
10	G3/8	3636 10 17
12	G3/8	3636 12 17
12	G1/2	3636 12 21

3618 Banjo équerre, BSP cylindrique et métrique



ØD	C	Référence
4	M5 x 0.8	3618 04 19
4	G1/8	3618 04 10
6	M5 x 0.8	3618 06 19
6	G1/8	3618 06 10
6	G1/4	3618 06 13
8	G1/8	3618 08 10
8	G1/4	3618 08 13
10	G3/8	3618 10 17

3639 Equerre égale, traversée de cloison



ØD	Référence
4	3639 04 00
6	3639 06 00
8	3639 08 00
10	3639 10 00
12	3639 12 00
14	3639 14 00

3602 Equerre égale



ØD	Référence
4	3602 04 00
6	3602 06 00
8	3602 08 00
10	3602 10 00
12	3602 12 00
14	3602 14 00

3604 Té égal



ØD	Référence
4	3604 04 00
6	3604 06 00
8	3604 08 00
10	3604 10 00
12	3604 12 00
14	3604 14 00