


3698 Té au centre, mâle BSPP et métrique

Laiton nickelé chimique FDA, FKM




ØD	C		E	F	G	H	J	L/2	Kg
4	M5x0,8	3698 04 19	3,5	10	10	27,5	7	18	0,018
	G1/8	3698 04 10	4,5	13	10	25,5	7	18	0,021
6	G1/8	3698 06 10	4,5	13	12	31	8	21,5	0,031
	G1/4	3698 06 13	5,5	16	12	30,5	8	21,5	0,035
8	G1/8	3698 08 10	4,5	14	15	33,5	10	23,5	0,041
	G1/4	3698 08 13	5,5	16	15	34	10	23,5	0,045
10	G1/4	3698 10 13	5,5	18	17,5	42	12	29	0,066
12	G3/8	3698 12 17	5,5	20	19,5	46	15	31	0,088
14	G1/2	3698 14 21	7	24	21,5	49	16	34	0,119

Raccord orientable.

3693 Té en bout, mâle BSPP et métrique

Laiton nickelé chimique FDA, FKM




ØD	C		E	F	G	H	H1	J	L	Kg
4	M5x0,8	3693 04 19	3,5	10	10	22,5	18	7	23	0,019
	G1/8	3693 04 10	4,5	13	10	20,5	18	7	23	0,021
6	G1/8	3693 06 10	4,5	13	12	25	21,5	8	28	0,031
	G1/4	3693 06 13	5,5	16	12	24,5	21,5	8	28	0,035
8	G1/8	3693 08 10	4,5	14	15	26,5	23,5	10	31	0,041
	G1/4	3693 08 13	5,5	16	15	26,5	23,5	10	31	0,044
10	G1/4	3693 10 13	5,5	18	17,5	33	29	12	37,5	0,066
12	G3/8	3693 12 17	5,5	20	19,5	36,5	31	15	40,5	0,090
14	G1/2	3693 14 21	7	24	21,5	38,5	34	16	45	0,112

Raccord orientable.

3618 Banjo simple, mâle BSPP et métrique

Laiton nickelé chimique FDA, FKM



ØD	C		F	H	H1	J	L1	L2	Kg
4	M5x0,8	3618 04 19	8	13	6	10	6	18,5	0,011
	G1/8	3618 04 10	13	16,5	7	15	7,5	22	0,029
6	M5x0,8	3618 06 19	8	13	6	10	5	22,5	0,015
	G1/8	3618 06 10	13	16,5	7	15	7,5	24	0,031
	G1/4	3618 06 13	17	21	9	18	9	24	0,049
8	G1/8	3618 08 10	13	16,5	7	15	7,5	25,5	0,033
	G1/4	3618 08 13	17	21	9	18	9	26,5	0,051
10	G3/8	3618 10 17	20	24,5	11	21,5	11	33	0,105

Température maximum : +80°C