


Raccords instantanés LF 3800 / Raccords d'implantation

3805 Piquage droit, mâle NPT

Inch

Acier inox 316L, FKM




ØD	C		F	F1	H	Kg
3/16	NPT1/8	3805 55 11	10	3	15,5	0,010
1/4	NPT1/8	3805 56 11	13	4	19	0,012
	NPT1/4	3805 56 14	14	4	17,5	0,017
3/8	NPT1/4	3805 60 14	19	6	25	0,029
	NPT3/8	3805 60 18	19	7	24	0,031
	NPT1/4	3805 62 14	22	7	26	0,036
1/2	NPT3/8	3805 62 18	22	8	25	0,041
	NPT1/2	3805 62 22	22	10	25	0,049

5/32"(4 mm) et 5/16"(8 mm) également disponibles

3801 Piquage droit, mâle BSPP et métrique


Acier inox 316L, FKM



ØD	C		F	F1	H	Kg
4	M5x0,8	3801 04 19	10	2,5	17	0,005
	G1/8	3801 04 10	13	3	16,5	0,009
6	M5x0,8	3801 06 19	13	2,5	20,5	0,010
	G1/8	3801 06 10	13	4	18	0,010
	G1/4	3801 06 13	17	4	18	0,015
8	G1/8	3801 08 10	15	5	19	0,013
	G1/4	3801 08 13	17	5	20,5	0,017
	G3/8	3801 08 17	21	6	20	0,027
10	G1/4	3801 10 13	19	7	25	0,025
	G3/8	3801 10 17	21	7	25	0,034
12	G1/4	3801 12 13	21	7	27	0,030
	G3/8	3801 12 17	21	9	26,5	0,034

3821 Adaptateur encliquetable, mâle BSPT


Acier inox 316L



ØD	C		F	H	Kg
4	R1/8	3821 04 10	10	21	0,006
	R1/8	3821 06 10	10	23	0,007
6	R1/4	3821 06 13	14	24	0,015
	R1/8	3821 08 10	11	24	0,008
8	R1/4	3821 08 13	14	25	0,016
	R1/4	3821 10 13	19	30	0,017
10	R3/8	3821 10 17	19	30	0,022
	R1/4	3821 12 13	19	31	0,017
12	R3/8	3821 12 17	19	31	0,022
	R1/2	3821 12 21	22	32	0,037

3821 Adaptateur encliquetable, mâle NPT

Acier inox 316L




ØD	C		F	H	Kg
4	NPT1/8	3821 04 11	10	21	0,006
6	NPT1/8	3821 06 11	10	23	0,007
	NPT1/4	3821 06 14	14	24	0,016
8	NPT1/8	3821 08 11	14	24	0,008
	NPT1/4	3821 08 14	14	25	0,016
10	NPT1/4	3821 10 14	14	30	0,018
	NPT3/8	3821 10 18	17	30	0,010
12	NPT1/4	3821 12 14	14	31	0,018

3821 Adaptateur encliquetable, mâle NPT

Inch

Acier inox 316L




ØD	C		F	H	Kg
1/4	NPT1/8	3821 56 11	10	26	0,009
	NPT1/4	3821 56 14	14	27	0,016
3/8	NPT1/4	3821 60 14	19	32	0,018
	NPT3/8	3821 60 18	19	32	0,028
	NPT1/4	3821 62 14	19	36	0,020
1/2	NPT3/8	3821 62 18	19	37	0,025
	NPT1/2	3821 62 22	22	37	0,042

5/32"(4 mm) et 5/16"(8 mm) également disponibles

3831 Adaptateur encliquetable, mâle BSPP et métrique

Acier inox 316L, FKM



ØD	C		F	H	Kg
4	M5x0,8	3831 04 19	10	23,5	0,004
	G1/8	3831 04 10	13	22	0,008
6	G1/8	3831 06 10	13	24	0,009
	G1/4	3831 06 13	17	24	0,015
8	G1/8	3831 08 10	13	25	0,010
	G1/4	3831 08 13	17	27	0,019
	G3/8	3831 08 17	21	27	0,024
10	G1/4	3831 10 13	17	32	0,021
	G3/8	3831 10 17	21	32	0,025
	G1/4	3831 12 13	17	33	0,021
12	G3/8	3831 12 17	21	33	0,028
	G1/2	3831 12 21	24	36	0,043

Les adaptateurs encliquetables 3821, 3921, 3831 et 3831 permettent, grâce à leur souplesse d'utilisation :

- de limiter la gamme de raccords à stocker
- d'implanter des raccords en té ou en équerre selon le besoin

