


6106 Union égale


Laiton, NBR



ØD		F1	F2	L	Kg
4	6106 04 00	13	11	34	0,025
6	6106 06 00	17	14	39	0,044
8	6106 08 00	19	17	46	0,069

6104 Té égal


Laiton, NBR



ØD		F	G	H	L/2	Kg
4	6104 04 00	11	12,5	26,5	20	0,034
6	6104 06 00	14	16	36	25,5	0,081
8	6104 08 00	17	19	39	30	0,111

0138 Joint cuivre pour filetage

Cuivre



C		G1	G2	K	Kg
M6	0138 06 00	6.2	9.9	1	0,033
M8	0138 08 00	8.2	11.4	1	0,001
G1/8	0138 10 00	10.2	13.4	1	0,001
M12	0138 12 00	12.2	15.4	1,5	0,001
M14	0138 14 00	14.2	17.9	1,5	0,001
M16	0138 16 00	16.2	19.9	1,5	0,001
M18	0138 18 00	18.2	21.9	1,5	0,001
M20	0138 20 00	20.2	23.9	1,5	0,001
M22	0138 22 00	22.2	26.9	1,5	0,002
M24	0138 24 00	24.3	28.9	2	0,003
M26	0138 26 00	26.3	30.9	2	0,003
M30	0138 30 00	30.3	37.9	2	0,004
M36	0138 36 00	36.3	41.9	2	0,005
G1/4	0138 13 00	13.2	17.9	1,5	0,001
G3/8	0138 17 00	17.2	20.9	1,5	0,001
G1/2	0138 21 00	21.1	25.9	1,5	0,002
G3/4	0138 27 00	27.3	31.9	2	0,003
G1	0138 33 00	33.3	38.9	2	0,005
G1 1/4	0138 42 00	42.3	48.9	2	0,007
G2	0138 60 00	60.5	67.8	2,5	0,014

DIN 7603
ISO 65061