


6300 Cartouche monobloc LIQUIfit®

Inch

Laiton, EPDM




ØD			G	G1	H	L	Kg
1/4	6300 56 00		10,5	14,5	12,5	600	0,002
3/8	6300 60 00		15,5	19	17	930	0,005
1/2	6300 62 00		22	25	23	1 038	0,011

50 cartouches par étui Carstick®


5/32" (4mm) et 5/16" (8 mm) également disponibles.

Merci de nous consulter pour obtenir le plan détaillé nécessaire à la réalisation des logements, ainsi que leurs matériaux



6579 Équerre fixe, mâle BSPT

Bio-polymère, EPDM




ØD	C		G	H	J	L	Kg
	R1/8	6579 06 10WP2	11	14	10	19	0,002
6	R1/4	6579 06 13WP2	11	14	10	19	0,003
	R3/8	6579 06 17WP2	11	14	10	19	0,004

Filetage sans pré-coating.

6579 Équerre fixe, mâle NPTF

Inch

Bio-polymère, EPDM




ØD	C		G	H	J	L	Kg
	NPT1/8	6579 56 11WP2	11	22	3/8	18	0,009
1/4	NPT1/4	6579 56 14WP2	11	26	3/8	18	0,003
3/8	NPT1/4	6579 60 14WP2	16	32	1/2	26	0,006

Filetage sans pré-coating.

6579 Équerre fixe, mâle BSPT

Inch

Bio-polymère, EPDM



ØD	C		G	H	J	L	Kg
1/4	R1/4	6579 56 13WP2	11	26	10	18	0,003
3/8	R3/8	6579 60 17WP2	16	32	13	26	0,006

Filetage sans pré-coating.

6599 Piquage droit, mâle BSPP

POM, EPDM



ØD	C		E	F	G	H	Kg
	G1/8	6599 06 10WP2	6	17	15	24,5	0,007
6	G1/4	6599 06 13WP2	8,5	18	15	33	0,008
	G1/8	6599 08 10WP2	6	18	17,5	26	0,010
8	G1/4	6599 08 13WP2	8,5	18	17,5	26	0,011
	G3/8	6599 08 17WP2	9	22	17,5	26	0,012
	G1/4	6599 10 13WP2	8,5	22	20	29,5	0,015
10	G3/8	6599 10 17WP2	9	22	20	29,5	0,015
	G1/2	6599 10 21WP2	12,5	26	20	29,5	0,019
	G3/8	6599 12 17WP2	9	26	23	34,5	0,023
12	G1/2	6599 12 21WP2	12,5	26	23	34,5	0,025


Technologie à pince.

Filetage sans pré-coating ; corps orientable.

Raccord certifié NSF seulement

6509 Équerre, mâle BSPT

Bio-polymère, EPDM




ØD	C		F	G	H	L	Kg
	R1/8	6509 06 10WP2	13	10,5	28	24	0,037
6	R1/4	6509 06 13WP2	14	10,5	28	24	0,007
	R3/8	6509 06 17WP2	17	10,5	28	24	0,008
	R1/8	6509 08 10WP2	19	13,5	34	29,5	0,010
8	R1/4	6509 08 13WP2	19	13,5	34	29,5	0,011
	R3/8	6509 08 17WP2	19	13,5	34	29,5	0,011
	R1/4	6509 10 13WP2	19	16	38	34,5	0,019
10	R3/8	6509 10 17WP2	19	16	38	34,5	0,020
	R1/2	6509 10 21WP2	22	16	38	34,5	0,023
	R3/8	6509 12 17WP2	22	19	44	40	0,022
12	R1/2	6509 12 21WP2	22	19	44	40	0,024

Filetage sans pré-coating ; raccord orientable.

6509 Équerre, mâle NPTF

Inch

Bio-polymère, EPDM



ØD	C		F	G	H	L	Kg
	NPT1/8	6509 56 11WP2	1/2	11	28	23,5	0,003
1/4	NPT1/4	6509 56 14WP2	9/16	11	28	23,5	0,004
	NPT3/8	6509 56 18WP2	3/4	11	28,5	23,5	0,006

Filetage sans pré-coating ; raccord orientable.