


Raccords instantanés LIQUIfit® avec embase métallique

6959 Équerre, mâle BSPP et métrique

Bio-polymère, acier inox 316L, EPDM




ØD	C		E	F	G	H	L	Kg
4	M5x0,8	6959 04 19	3,5	10	8,5	23	19	0,009
	G1/8	6959 04 10	4,5	13	8,5	22,5	19	0,009
	G1/4	6959 04 13	5,5	16	8,5	22,5	19	0,014
6	M5x0,8	6959 06 19	3,5	10	10,5	26,5	22,5	0,008
	G1/8	6959 06 10	4,5	13	10,5	26,5	22,5	0,011
	G1/4	6959 06 13	5,5	16	10,5	26,5	22,5	0,016
8	G1/8	6959 08 10	4,5	13	13,5	35	29,5	0,018
	G1/4	6959 08 13	5,5	16	13,5	33	29,5	0,020
	G3/8	6959 08 17	5,5	21	13,5	33	29,5	0,028
10	G1/4	6959 10 13	5,5	16	16	40,5	34	0,029
	G3/8	6959 10 17	5,5	21	16	39	34	0,037
	G1/2	6959 10 21	7	24	16	39	34	0,042
12	G1/4	6959 12 13	5,5	19	19	44	40	0,042
	G3/8	6959 12 17	5,5	21	19	42	40	0,040
	G1/2	6959 12 21	7	24	19	42	40	0,049
16	G3/8	6959 16 17	7,5	27	27	54	52	0,088
	G1/2	6959 16 21	9	27	27	55	52	0,084
	G3/4	6959 16 27	10,5	32	27	55	52	0,120

Raccord orientable.

6974 Piquage droit, femelle BSPP


Acier inox 316L, EPDM



ØD	C		E	F	H	Kg
4	G3/8	6974 16 17	17	27	44	0,060
	G1/2	6974 16 21	21,5	27	17	0,065
	G3/4	6974 16 27	19	32	47	0,097

6958 Té au centre, mâle BSPP et métrique

Bio-polymère, acier inox 316L, EPDM




ØD	C		E	F	G	H	L/2	Kg
4	G1/8	6958 04 10	5	13	8,5	22	14	0,009
	G1/4	6958 04 13	5,5	16	8,5	22	14	0,014
6	G1/8	6958 06 10	5	13	10,5	28,5	16	0,011
	G1/4	6958 06 13	5,5	16	10,5	28,5	16	0,016
8	G1/8	6958 08 10	4,5	13	13,5	38	23	0,019
	G3/8	6958 08 17	5,5	21	13,5	36	23	0,030
10	G1/4	6958 10 13	5,5	16	16	43	26,5	0,032
	G3/8	6958 10 17	5,5	21	16	43	26,5	0,055
	G1/2	6958 10 21	7,5	24	16	43	26,5	0,051
12	G3/8	6958 12 17	5,5	21	19	45,5	31	0,042
	G1/2	6958 12 21	7	24	19	45,5	31	0,049

Raccord orientable

6979 Équerre, mâle BSPT

Bio-polymère, acier inox 316L, EPDM




ØD	C		F	G	H	L	Kg
4	R1/8	6979 04 10	10	8,5	23	19	0,008
	R1/4	6979 04 13	14	8,5	23,5	19	0,018
6	R1/8	6979 06 10	10	10,5	27	22,5	0,010
	R1/4	6979 06 13	14	10,5	27,5	22,5	0,020
8	R1/8	6979 08 10	13	13,5	33,5	29,5	0,018
	R1/4	6979 08 13	14	13,5	32,5	29,5	0,022
	R3/8	6979 08 17	17	13,5	33	29,5	0,032
10	R1/4	6979 10 13	15	16	39,5	34	0,031
	R3/8	6979 10 17	17	16	39,5	34	0,041
	R1/2	6979 10 21	21	16	39,5	34	0,060
12	R3/8	6979 12 17	19	19	45,5	40,5	0,051
	R1/2	6979 12 21	21	19	45,5	40,5	0,065

Raccord orientable

6989 Équerre, mâle BSPP et métrique

Bio-polymère, laiton nickelé, NBR



ØD	C		E	F	G	H	L	Kg
4	M5x0,8	6989 04 19	3,5	8	8,5	13,5	14	0,002
	G1/8	6989 04 10	5	13	8,5	13	14	0,006
	G1/4	6989 04 13	5,5	16	8,5	13	14	0,011
6	M5x0,8	6989 06 19	3,5	8	10,5	15,5	16	0,003
	G1/8	6989 06 10	5	13	10,5	15	16	0,006
	G1/4	6989 06 13	5,5	16	10,5	15	16	0,011
8	G1/8	6989 08 10	4,5	13	13,5	20,5	23	0,009
	G1/4	6989 08 13	5,5	16	13,5	18,5	23	0,012
	G3/8	6989 08 17	5,5	20	13,5	18,5	23	0,017
10	G1/4	6989 10 13	5,5	16	16	23,5	26,5	0,014
	G3/8	6989 10 17	5,5	20	16	22	26,5	0,017
	G1/4	6989 12 13	5,5	16	19	26,5	31	0,016
12	G3/8	6989 12 17	5,5	20	19	25	31	0,019
	G1/2	6989 12 21	7	24	19	25	31	0,029

Raccord orientable

*Joint bi-matière