


6316 Union traversée de cloison égale


Bio-polymère, EPDM



ØD		F	K max	L	L1	ØT min	Kg
4	6316 04 00WP2	13	5,5	15,5	10,5	10,5	0,018
6	6316 06 00WP2	15	8,5	20	10	12,5	0,004
8	6316 08 00WP2	18	14,5	27	10,5	15,5	0,007
10	6316 10 00WP2	22	14,5	30	13	18,5	0,012
12	6316 12 00WP2	26	18,5	35	15,5	22,5	0,020

6316 Union traversée de cloison égale Inch

Bio-polymère, EPDM




ØD		F	K max	L	L1	ØT min	Kg
1/4	6316 56 00WP2	15	8,5	20	10	12,5	0,004
3/8	6316 60 00WP2	22	14,5	29,5	12,5	18,5	0,012
1/2	6316 62 00WP2	29	20,5	40,5	17	25,5	0,030

5/32" (4mm) et 5/16" (8mm) sont aussi disponibles

6976 Union traversée de cloison

Acier inox 316L, EPDM



ØD		F	K max	L1	L2	ØT min	Kg
16	6976 16 00	32	10,5	33	30	27,5	0,166

Indice de protection électrique IP55

Gammes complémentaires LIQUIfit®

Les autres produits de la gamme LIQUIfit® sont présentés dans ce catalogue dans les chapitres correspondants :

Tubes et tuyaux techniques

PE Advanced



Raccords à fonctions

Clapet anti-retour



Robinets industriels

LIQUIfit®

