




550H • 540N • 560 • 510A • 518C • 1202LT • 55LT • 2040N •
2040H • 520N • 528N • 580N • 588N • 590 • 575X

Embouts
1D956 – 10656

1D956 – Mâle BSP cylindrique DIN 3852 forme A




MATÉRIAUX Acier, galvanisé, passivé transparent sans Cr(VI).
Autres matériaux disponibles sur demande.

Référence #	DN Mod mm Pouce				Type de raccordement		A mm	B mm	H mm	Max. WP MPa
	DN	Mod	mm	Pouce	Filetage	Tube d. ext. pouce				
1D956-4-4	6	-04	6,4	1/4	G 1/4	1/4	52	27	19	63,0
1D956-6-5	8	-05	7,9	5/16	G 3/8	3/8	53	27	22	55,0
1D956-6-6	10	-06	9,5	3/8	G 3/8	3/8	53	28	22	55,0
1D956-8-8	12	-08	12,7	1/2	G 1/2	1/2	60	32	27	43,0
1D956-12-12	20	-12	19,0	3/4	G 3/4	3/4	75	42	32	35,0

Série 56

10656 – Femelle tournant SAE (JIC) 37° filetage UNF



MATÉRIAUX Acier, galvanisé, passivé transparent sans Cr(VI).
Autres matériaux disponibles sur demande.

Référence #	DN Mod mm Pouce				Type de raccordement		A mm	B mm	H mm	J mm	Max. WP MPa
	DN	Mod	mm	Pouce	Filetage	Tube d. ext. pouce					
10656-4-3	5	-03	4,8	3/16	7/16 - 20UNF	1/4	36	19	12	17	41,0
10656-4-4	6	-04	6,4	1/4	7/16 - 20UNF	1/4	44	19	14	17	41,0
10656-5-4	6	-04	6,4	1/4	1/2 - 20UNF	5/16	44	20	14	17	41,0
10656-6-4	6	-04	6,4	1/4	9/16 - 18UNF	3/8	45	20	14	19	34,5
10656-6-5	8	-05	7,9	5/16	9/16 - 18UNF	3/8	47	21	17	19	34,5
10656-6-6	10	-06	9,5	3/8	9/16 - 18UNF	3/8	47	22	17	19	34,5
10656-8-6	10	-06	9,5	3/8	3/4 - 16UNF	1/2	49	24	19	22	34,5
10656-8-8	12	-08	12,7	1/2	3/4 - 16UNF	1/2	54	27	22	22	34,5