




550H • 540N • 560 • 510A • 518C • 1202LT • 55LT • 2040N •
2040H • 520N • 528N • 580N • 588N • 590 • 575X

Embouts
19256 – 1B156

19256 – Femelle tournant BSP 60°




MATÉRIAUX Acier, galvanisé, passivé transparent sans Cr(VI).
Autres matériaux disponibles sur demande.

Référence #	DN Mod mm Pouce				Type de raccordement		A mm	B mm	J mm	Max. WP MPa
					Filetage 	Tube d. ext. pouce 				
19256-4-3	5	-03	4,8	3/16	G 1/4	1/4	37	19	19	63,0
19256-2-4	6	-04	6,4	1/4	G 1/8	1/8	43	18	14	35,0
19256-4-4	6	-04	6,4	1/4	G 1/4	1/4	44	20	19	63,0
19256-6-4	6	-04	6,4	1/4	G 3/8	3/8	44	20	22	55,0
19256-4-5	8	-05	7,9	5/16	G 1/4	1/4	45	20	19	63,0
19256-6-5	8	-05	7,9	5/16	G 3/8	3/8	45	20	22	55,0
19256-6-6	10	-06	9,5	3/8	G 3/8	3/8	45	20	22	55,0
19256-8-6	10	-06	9,5	3/8	G 1/2	1/2	47	22	27	43,0
19256-8-8	12	-08	12,7	1/2	G 1/2	1/2	51	22	27	43,0
19256-10-8	12	-08	12,7	1/2	G 5/8	5/8	49	22	30	37,5
19256-12-12	20	-12	19,0	3/4	G 3/4	3/4	58	24	32	35,0
19256-16-16	25	-16	25,4	1	G 1	1	73	26	41	28,0

Série 56

1B156 – Femelle tournant BSP 60° coude 45°



MATÉRIAUX Acier, galvanisé, passivé transparent sans Cr(VI).
Autres matériaux disponibles sur demande.

Référence #	DN Mod mm Pouce				Type de raccordement		A mm	B mm	E mm	J mm	Max. WP MPa
					Filetage 	Tube d. ext. pouce 					
1B156-4-3	5	-03	4,8	3/16	G 1/4	1/4	54	36	14	19	63,0
1B156-4-4	6	-04	6,4	1/4	G 1/4	1/4	62	38	16	19	63,0
1B156-6-5	8	-05	7,9	5/16	G 3/8	3/8	64	39	16	22	55,0
1B156-6-6	10	-06	9,5	3/8	G 3/8	3/8	66	41	17	22	55,0
1B156-8-8	12	-08	12,7	1/2	G 1/2	1/2	76	48	20	27	43,0
1B156-10-8	12	-08	12,7	1/2	G 5/8	5/8	75	48	19	30	37,5
1B156-12-12	20	-12	19,0	3/4	G 3/4	3/4	99	65	25	32	35,0