




1C956 – Femelle tournant métrique (24°/60°) avec joint torique

Série lourde – Écrou-raccord métrique – ISO 12151-2

MATÉRIAUX Acier galvanisé, passivé transparent sans Cr(VI).
Autres matériaux disponibles sur demande.




Référence #	DN Mod mm Pouce				Type de raccordement		A mm	B mm	J mm	Max. WP MPa
					Filetage 	Tube d. ext. mm 				
1C956-8-3	5	-03	4.8	3/16	M16x1.5	8	40.5	22.8	19	63.0
1C956-8-4	6	-04	6.4	1/4	M16x1.5	8	48.0	23.0	19	63.0
1C956-10-4	6	-04	6.4	1/4	M18x1.5	10	47.5	23.0	22	63.0
1C956-12-4	6	-04	6.4	1/4	M20x1.5	12	48.4	23.9	24	63.0
1C956-10-5	8	-05	7.9	5/16	M18x1.5	10	48.8	23.0	22	63.0
1C956-12-5	8	-05	7.9	5/16	M20x1.5	12	49.7	23.9	24	63.0
1C956-12-6	10	-06	9.5	3/8	M20x1.5	12	49.4	24.2	24	63.0
1C956-14-6	10	-06	9.5	3/8	M22x1.5	14	49.3	24.1	27	63.0
1C956-16-8	12	-08	12.7	1/2	M24x1.5	16	55.7	27.3	30	42.0
1C956-25-12	20	-12	19.0	3/4	M36x2	25	66.0	32.1	46	42.0

10C56 – Femelle tournant métrique (24°/60°) avec joint torique

Coude 45° – Série lourde – Écrou-raccord métrique – ISO 12151-2

MATÉRIAUX Acier galvanisé, passivé transparent sans Cr(VI).
Autres matériaux disponibles sur demande.



Référence #	DN Mod mm Pouce				Type de raccordement		A mm	B mm	E mm	J mm	Max. WP MPa
					Filetage 	Tube d. ext. mm 					
10C56-8-3	5	-03	4.8	3/16	M16x1.5	8	59.0	41.0	18.0	19	63.0
10C56-10-4	6	-04	6.4	1/4	M18x1.5	10	63.8	39.3	17.0	22	63.0
10C56-12-5	8	-05	7.9	5/16	M20x1.5	12	98.7	42.9	17.2	24	63.0
10C56-12-6	10	-06	9.5	3/8	M20x1.5	12	74.6	49.4	20.0	24	63.0
10C56-16-8	12	-08	12.7	1/2	M24x1.5	16	79.5	51.0	23.0	30	42.0