




550H • 540N • 560 • 510A • 518C • 1202LT • 55LT • 2040N •
2040H • 520N • 528N • 580N • 588N • 590 • 575X

Embouts
1D056 – 1D256

1D056 – Mâle métrique fixe 24° série légère – ISO 12151-2

MATÉRIAUX Acier, galvanisé, passivé transparent sans Cr(VI).
Autres matériaux disponibles sur demande.




Référence #	DN Mod mm Pouce				Type de raccordement		A mm	B mm	H mm	Max. WP MPa
	DN	Mod	mm	Pouce	Filetage	Tube d. ext. mm				
1D056-6-3	5	-03	4,8	3/16	M12x1,5	6	41	23	12	25,0
1D056-8-4	6	-04	6,4	1/4	M14x1,5	8	48	23	14	42,5
1D056-10-5	8	-05	7,9	5/16	M16x1,5	10	50	24	17	40,0
1D056-12-5	8	-05	7,9	5/16	M18x1,5	12	52	26	19	35,0
1D056-10-6	10	-06	9,5	3/8	M16x1,5	10	50	25	17	40,0
1D056-12-6	10	-06	9,5	3/8	M18x1,5	12	52	26	19	35,0
1D056-15-6	10	-06	9,5	3/8	M22x1,5	15	53	27	22	31,0
1D056-15-8	12	-08	12,7	1/2	M22x1,5	15	56	28	24	31,0
1D056-18-12	20	-12	19,0	3/4	M26x1,5	18	66	33	27	28,0
1D056-22-12	20	-12	19,0	3/4	M30x2	22	67	33	32	28,0
1D056-28-16	25	-16	25,4	1	M36x2	28	84	36	36	21,0

Série 56

1D256 – Mâle métrique fixe 24° série lourde – ISO 12151-2

MATÉRIAUX Acier, galvanisé, passivé transparent sans Cr(VI).
Autres matériaux disponibles sur demande.



Référence #	DN Mod mm Pouce				Type de raccordement		A mm	B mm	H mm	Max. WP MPa
	DN	Mod	mm	Pouce	Filetage	Tube d. ext. mm				
1D256-8-3	5	-03	4,8	3/16	M16x1,5	8	43	25	17	63,0
1D256-10-4	6	-04	6,4	1/4	M18x1,5	10	52	27	19	63,0
1D256-12-5	8	-05	7,9	5/16	M20x1,5	12	53	27	22	63,0
1D256-14-6	10	-06	9,5	3/8	M22x1,5	14	57	31	24	63,0
1D256-16-6	10	-06	9,5	3/8	M24x1,5	16	57	31	24	42,0
1D256-16-8	12	-08	12,7	1/2	M24x1,5	16	60	32	24	42,0
1D256-20-12	20	-12	19,0	3/4	M30x2	20	72	39	32	42,0