



1J956 – Femelle tournant ORFS O-Lok®
Coude 90° – Écrou-raccord UNF – ISO 12151-1

MATÉRIAUX Acier galvanisé, passivé transparent sans Cr(VI).
Autres matériaux disponibles sur demande.

Référence #	DN Mod mm Pouce				Type de raccordement		A mm	B mm	E mm	J mm	Max. WP MPa
	Filetage	Tube ext. pouce	Filetage	Tube ext. pouce							
1J956-4-3-SM	5	-03	4.8	3/16	9/16 - 18 UNF	1/4	46.0	28.3	21	17	41.0
1J956-4-4-SM	6	-04	6.4	1/4	9/16 - 18 UNF	1/4	54.0	26.5	21	17	41.0
1J956-6-4-SM	6	-04	6.4	1/4	11/16 - 16 UNF	3/8	54.5	30.0	23	22	41.0
1J956-6-5-SM	8	-05	7.9	5/16	11/16 - 16 UNF	3/8	57.8	32.0	23	22	41.0
1J956-6-6-SM	10	-06	9.5	3/8	11/16 - 16 UNF	3/8	56.3	31.1	23	22	41.0
1J956-8-8-SM	12	-08	12.7	1/2	13/16 - 16 UNF	1/2	63.0	34.6	29	24	41.0
1J956-10-8-SM	12	-08	12.7	1/2	1 - 14 UNF	5/8	71.0	42.0	32	30	41.0
1J956-12-12-SM	20	-12	19.0	3/4	1 3/16 - 12 UNF	3/4	99.0	65.0	48	36	41.0
1J956-16-16-SM	25	-16	25.4	1	1 7/16 - 12 UNF	1	110.8	63.0	56	41	41.0

1J056 – Mâle ORFS O-Lok®
ISO 12151-1

MATÉRIAUX Acier galvanisé, passivé transparent sans Cr(VI).
Autres matériaux disponibles sur demande.

Référence #	DN Mod mm Pouce				Type de raccordement		A mm	B mm	H mm	Max. WP MPa
	Filetage	Tube ext. pouce	Filetage	Tube ext. pouce						
1J056-4-4-SM	6	-04	6.4	1/4	9/16 - 18 UNF	1/4	42.9	24.7	17	41.0
1J056-6-6-SM	10	-06	9.5	3/8	11/16 - 16 UNF	3/8	52.3	28.1	19	41.0
1J056-8-6-SM	10	-06	9.5	3/8	13/16 - 16 UNF	1/2	54.6	29.4	22	41.0
1J056-8-8-SM	12	-08	12.7	1/2	13/16 - 16 UNF	1/2	55.4	27.0	22	41.0