







# Raccords auto-obturants et tournants

## 3391 Piquage droit auto-obturant, mâle BSPP

	Laiton nickelé, NBR 	<b>ØD</b>	<b>C</b>		<b>E</b>	<b>F</b>	<b>H</b>	<b>H1</b>	<b>H2</b>	<b>ØT</b>	<b>kg</b>
		4	G1/8	<a href="#">3391 04 10</a>	5	13	18	7,5	6	5	0,017
		6	G1/8	<a href="#">3391 06 10</a>	5	14	19,5	9	6	7,5	0,019
		8	G1/8	<a href="#">3391 08 10</a>	5	14	29,5	10	6	7,5	0,025
			G1/4	<a href="#">3391 08 13</a>	5,5	16	25,5	11	8	9	0,032
10	G3/8	<a href="#">3391 10 17</a>	5,5	20	27,5	13	11	10	0,055		




Pression de service maximum : 10 bar

## 3091 Piquage droit auto-obturant, mâle BSPT




	Laiton nickelé, NBR 	<b>ØD</b>	<b>C</b>		<b>E</b>	<b>F</b>	<b>H</b>	<b>H1</b>	<b>ØT</b>	<b>kg</b>
		4	R1/8	<a href="#">3091 04 10</a>	7,5	12	18	9,5	5	0,015
		6	R1/8	<a href="#">3091 06 10</a>	7,5	13	19,5	9,5	7,5	0,015
		8	R1/8	<a href="#">3091 08 10</a>	6,5	14	25	10,5	7,5	0,024
			R1/4	<a href="#">3091 08 13</a>	11	14	25,5	13,5	9	0,021
10	R3/8	<a href="#">3091 10 17</a>	11,5	17	27,5	14	10	0,035		

Pression de service maximum : 10 bar  
Filetage avec pré-coating

## 3160 Auto-obturant encliquetable




	Polymère technique, NBR 	<b>ØD</b>		<b>L</b>	<b>L1</b>	<b>kg</b>
		4	<a href="#">3160 04 00</a>	46	33,5	0,006
		6	<a href="#">3160 06 00</a>	53,5	31	0,009
		8	<a href="#">3160 08 00</a>	58	31	0,014

## 3159 Equerre oscillante, mâle BSPT

	Polymère technique, laiton nickelé, NBR 	<b>ØD</b>	<b>C</b>		<b>F</b>	<b>G</b>	<b>H</b>	<b>L</b>	<b>kg</b>
		4	R1/8	<a href="#">3159 04 10</a>	12	11	22	17,5	0,012
			R1/8	<a href="#">3159 06 10</a>	14	14	26,5	20,5	0,014
		6	R1/4	<a href="#">3159 06 13</a>	14	14	23,5	20,5	0,022
			R1/8	<a href="#">3159 08 10</a>	17	16	32	23,5	0,036
		8	R1/4	<a href="#">3159 08 13</a>	17	16	29	23,5	0,037
			R3/8	<a href="#">3159 08 17</a>	17	16	25	23,5	0,033
		10	R1/4	<a href="#">3159 10 13</a>	19	19,5	37,5	29	0,053
			R3/8	<a href="#">3159 10 17</a>	19	19,5	33,5	29	0,045
		12	R1/4	<a href="#">3159 12 13</a>	21	22	44,5	33,5	0,080
			R3/8	<a href="#">3159 12 17</a>	21	22	41	33,5	0,070

Filetage avec pré-coating

## 3189 Equerre oscillante, mâle BSPP et métrique

	Polymère technique, laiton nickelé, NBR 	<b>ØD</b>	<b>C</b>		<b>E</b>	<b>F</b>	<b>G</b>	<b>H</b>	<b>L</b>	<b>kg</b>
		4	M5x0,8	<a href="#">3189 04 19</a>	3	12	11	24,5	17,5	0,012
			G1/8	<a href="#">3189 04 10</a>	5	13	11	23	17,5	0,013
			M5x0,8	<a href="#">3189 06 19</a>	3	12	14	27,5	20,5	0,017
		6	G1/8	<a href="#">3189 06 10</a>	5	14	14	27	20,5	0,019
			G1/4	<a href="#">3189 06 13</a>	5,5	16	14	25,5	20,5	0,023
		8	G1/8	<a href="#">3189 08 10</a>	5	17	16	31	23,5	0,034
			G1/4	<a href="#">3189 08 13</a>	5,5	17	16	31	23,5	0,034
		8	G3/8	<a href="#">3189 08 17</a>	5,5	20	16	29,5	23,5	0,042
			G1/4	<a href="#">3189 10 13</a>	5,5	19	19,5	39	29	0,058
		10	G3/8	<a href="#">3189 10 17</a>	5,5	20	19,5	37	29	0,050
			G1/4	<a href="#">3189 12 13</a>	5,5	21	22	46,5	33,5	0,074
		12	G3/8	<a href="#">3189 12 17</a>	5,5	21	22	45,5	33,5	0,072