


01

Mâle NPTF

SAE J476A / J516 – AGN




Référence	D. Int. du tuyau				Filetage NPTF	A mm	B mm	H mm
	DN	pouce	module	mm				
10177-8-8	12	1/2	-8	12,7	1/2x14	69	35	22
10177-8-12	19	3/4	-12	19,1	1/2x14	87	41	30
10177-12-12	19	3/4	-12	19,1	3/4x14	87	41	30
10177-16-16	25	1	-16	25,4	1x11 1/2	103	49	36
10177-20-20	31	1 1/4	-20	31,8	1 1/4x11	116	53	46
10177-24-24	38	1 1/2	-24	38,1	1 1/2x11	124	57	50
10177-32-32	51	2	-32	50,8	2x11	143	66	65

03

Mâle JIC 37°

ISO12151-5-S – AGJ



Référence	D. Int. du tuyau				Filetage UNF	A mm	B mm	H mm
	DN	pouce	module	mm				
10377-8-8	12	1/2	-8	12,7	3/4x16	66,45	32	22
10377-10-8	12	1/2	-8	12,7	7/8x14	69	34	24
10377-10-10	16	5/8	-10	15,9	7/8x14	76	38	24
10377-12-10	16	5/8	-10	15,9	1 1/16x12	82	43	30
10377-12-12	19	3/4	-12	19,1	1 1/16x12	89	43	30
10377-16-12	19	3/4	-12	19,1	1 5/16x12	92	46	36
10377-16-16	25	1	-16	25,4	1 5/16x12	101,4	47	36
10377-20-16	25	1	-16	25,4	1 5/8x12	110	56	50
10377-20-20	31	1 1/4	-20	31,8	1 5/8x12	118	55	50
10377-32-32	51	2	-32	50,8	2 1/2x12	148	71	65

Série d'embouts compatible avec les tuyaux:

77 787TC 797TC