

Raccords filetés mâles GAZ, à douille hélicoïdale 2HP

DN	Ø sur douille	ALUMINIUM	ACIER INOX.
2	53,4	1740.529	1740.829
3	79,0	1740.547	1740.847T
4	104,2	1740.557	1740.857



Joint de sertissage

Joint à double lèvre pour raccords à douille hélicoïdale HM

DN	NBR - Buna (noir)	FPM - Viton (marron)
20	4040.111	-
25	4040.114	-
32	4040.115	-
40	4040.119	-
50	4040.122	4040.522
65	4040.126	4040.526
80	4040.129	4040.529
100	4040.131	4040.531



Jupes de sertissage

Jupes préformées à sertir radialement avec une presse équipée de mors concentriques ou par filage au travers d'une matrice.

DN	Ø int.	Ø DP	L	Cas d'emploi	ALUMINIUM	ACIER INOX.	ACIER ZINGUÉ
20	30,0	25,5	25,0	C	-	5002.810	-
20	35,0	22,5	37,0	C	-	5001.811	-
25	36,0	28,0	35,0	B	-	-	5001.914
25	41,0	27,0	44,0	C - E	5001.514T	-	-
25	42,0	27,5	42,0	C - E	-	5001.814	-
32	50,0	36,0	45,0	C - E	-	5001.815	-
40	56,0	41,0	62	C - D	5001.519T	-	-
40	56,0	43,5	52	C - D	5001.519	-	-
40	56,0	46,0	45	E	5002.519	-	-
40	57,0	43,5	52	C - D	-	5001.819	-
40	57,0	46,0	45	E	-	5002.819	-
50	66,0	55,0	45,0	E	5001.52245	-	-
50	66,0	55,0	63,0	C - E	5001.522	-	-
50	67,0	55,0	63,0	C - E	-	-	5001.922
50	67,0	65,0	63,0	C - E	-	5001.822	-
50	70,0	55,0	63,0	D - E	5001.522HP	5001.822HP	-
65	83,0	68,0	73,0	C	-	5001.826	5001.926
65	84,0	68,0	73,0	C - D	5001.526	-	-
65	84,0	70,5	55,0	E	5002.526	-	-
65	85,5	70,5	55	E	-	5002.826	-
65	86,0	68,0	73,0	D	-	5001.826HP	-
80	95,0	83,5	75,0	C - D	-	5001.829A	-
80	98,5	83,5	75	C - D	-	5001.829	5001.929
80	101,0	83,5	75,0	C - D	5001.529	-	-
80	101,0	90,5	75,0	E	-	5002.827	-
80	103,0	90,5	67,0	E	-	5002.829	-
80	104,0	90,5	75,0	E	5002.528	5002.828	-
80	106,0	90,5	75,0	E	-	5002.828A	-
80	111,0	85,0	110,0	E	-	5001.830	-
80	111,0	91,0	110,0	E	-	5001.830A	-
100	120,0	107,0	87,0	C - D - E	-	5001.831	-
100	122,0	107,0	87,0	C - D - E	5001.532	5001.832	-
100	126,0	107,0	87,0	C - D - E	5001.533	-	-
100	126,0	111,0	87,0	E	-	5002.833	-
100	130,0	107,0	87,0	C - D - E	5001.534	-	-
100	130,0	111,0	87,0	E	5002.531	5002.831	-

