



SIMATIC ET 200SP, BusAdapter BA 2xRJ45, 2 x connecteurs femelles RJ45

Informations générales			
Désignation du type de produit	BA 2x RJ45		
Interfaces			
Nombre d'interfaces PROFINET	1; 2 ports (commutateur) 2x RJ45		
Supporte le protocole pour PROFINET IO			
● Nombre de ports RJ45	2		
Longueur de câble			
— Câbles Cu	100 m		
Conditions ambiantes			
Température ambiante en service			
● Montage horizontal, mini	-30 °C		
● Montage horizontal, maxi	60 °C		
● Montage vertical, mini	-30 °C		
● Montage vertical, maxi	50 °C		
Altitude en service par rapport au niveau de la mer			
● Altitude d'installation, max.	5 000 m; restrictions pour altitude d'implantation > 2 000 m, voir Manuel système ET 200SP		
Dimensions			
Largeur	20 mm		
Hauteur	69,5 mm		
Profondeur	59 mm		
Poids			
Poids approx.	46 g		
Classifications			
		Version	Classification
	eClass	14	27-24-26-92
	eClass	12	27-24-26-92
	eClass	9.1	27-24-26-92
	eClass	9	27-24-26-92
	eClass	8	27-24-26-92
	eClass	7.1	27-24-26-92
	eClass	6	27-24-26-92
	ETIM	10	EC002584
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
	IDEA	4	3552

Homologations / Certificats

General Product Approval

[Manufacturer Declaration](#)[Miscellaneous](#)[KC](#)

General Product Approval

For use in hazardous locations

[FM](#)[CCC-Ex](#)

For use in hazardous locations

Maritime application

[Miscellaneous](#)[Type Examination Certificate](#)

Maritime application

Environment

[NK / Nippon Kaiji Kyokai](#)[CCS \(China Classification Society\)](#)

dernière modification :

09/10/2024