



SIMATIC ET 200SP, pièce de rechange Module serveur pour ET 200SP

Informations générales	
Désignation du type de produit	Module serveur
Version fonctionnelle du matériel	À partir de FS07
Conditions ambiantes	
Température ambiante en service	
• Montage horizontal, mini	-30 °C
• Montage horizontal, maxi	60 °C
• Montage vertical, mini	-30 °C
• Montage vertical, maxi	50 °C
Altitude en service par rapport au niveau de la mer	
• Altitude d'installation, max.	5 000 m; Restrictions pour altitude d'implantation > 2 000 m, voir manuel
Classifications	

	Version	Classification
eClass	14	27-24-26-92
eClass	12	27-24-26-92
eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Homologations / Certificats
General Product Approval



[Manufacturer Declaration](#)



[KC](#)



For use in hazardous locations



[CCC-Ex](#)

[FM](#)



[Miscellaneous](#)

For use in hazard-
ous locations

Maritime application

[Type Examination Cer-
tificate](#)



[NK / Nippon Kaiji Ky-
okai](#)

Maritime application



[CCS \(China Classifica-
tion Society\)](#)



dernière modification :

07/04/2025