

SIMATIC DP, module de connexion pour module d'interface PROFINET ET 200 pro, connexion 2xRJ45, 2x connecteur d'énergie Push pull pour PROFINET



Figure à titre d'exemple

Courant d'entrée			
sur tension d'alimentation 1L+, maxi	16 A; pas de consommation de courant, uniquement courant d'alim., max. 16 A avec déclassement		
sur tension de charge 2L+ (sans charge), maxi	16 A; pas de consommation de courant, uniquement courant d'alim., max. 16 A avec déclassement		
Accessoires			
Description des fonctions	Module de connexion IM PN, 2x RJ45, 2x PushPull		
fait partie du produit	IM154-4 PN HF		
Dimensions			
Largeur	90 mm		
Hauteur	130 mm		
Profondeur	51 mm		
Poids			
Poids approx.	325 g		
Classifications			
		Version	Classification
	eClass	14	27-24-26-03
	eClass	12	27-24-26-03
	eClass	9.1	27-24-26-03
	eClass	9	27-24-26-03
	eClass	8	27-24-26-03
	eClass	7.1	27-24-26-03
	eClass	6	27-24-26-03
	ETIM	10	EC001598
	ETIM	9	EC001598
	ETIM	8	EC001598
	ETIM	7	EC001598
	IDEA	4	3560
	UNSPSC	15	32-15-17-04

Homologations / Certificats	
General Product Approval	

[Manufacturer Declaration](#)



[Miscellaneous](#)



General Product Approval	Maritime application
--------------------------	----------------------

[KC](#)



[NK / Nippon Kaiji Kyokai](#)

Maritime application



[CCS \(China Classification Society\)](#)



dernière modification :

07/04/2025